





Device Specifications	Phaser 6022 WorkCentre 6027		
Output Speed			
Color 8.5 x 11 in. A4 / 210 x 297 mm 8.5 x 14 in. / 216 x 356 mm	Up to 18 ppm Up to 18 ppm Up to 14 ppm Up to 14 ppm	Up to 18 ppm Up to 18 ppm Up to 14 ppm	
Black-and-white 8.5 x 11 in. A4 / 210 x 297 mm 8.5 x 14 in. / 216 x 356 mm	Up to 18 ppm Up to 18 ppm Up to 14 ppm Up to 14 ppm	Up to 18 ppm Up to 18 ppm Up to 14 ppm	
Monthly Duty Cycle ¹	Up to 30,000 pages / month		
Recommended Average Monthly Print Volume ²	Up to 1,500 pages		
Memory	256 MB	512 MB	
Processor	525 MHz		
Connectivity	10/100Base-TX Ethernet Wi-Fi b/g/n Wi-Fi Direct High speed USB 2.0	10/100Base-TX Ethernet Wi-Fi b/g/n Wi-Fi Direct High speed USB 2.0	
Paper Handling			
Automatic Document Feeder (ADF)		
Capacity ³	NA	15 sheets	
Sizes		Custom Sizes: 5.8 x 8.3 in. to 8.5 x 14 in. / 148 x 210 mm to 216 x 356 mm	
Weights		16 lb. to 28 lb. bond / 60 to 105 gsm	
Bypass Tray			
Capacity ³	NA	NA	
Sizes			
Weights			
Media Types			
Main Tray			
Capacity ³	150 sheets		
Sizes	Sizes: 3 x 5 in. to 8.5 x 14 in. / 76 x 127 mm to 216 x 356 mm		
Weights	16 lb. bond to 60 lb. cover / 60 to 163 gsm		

Media Types Paper Output	Plain Bond Lightweight Cardstock Lightweight Glossy Card Stock Envelopes Labels Recycled Plain-Reloaded Bond-Reloaded Lightweight Card Stock Reloaded Lightweight Glossy Card Stock Reloaded Recycled-Reloaded		
Output Capacity ³	100 sheets (face-down)		
Print	Phaser 6022	WorkCentre 6027	
First-page-out Time	As fast as 13 seconds color / 12 seconds black-and-white	As fast as 13 seconds color / 12 seconds black-and-white	
Resolution	Up to 1200 x 2400 dpi enhanced image quality		
Maximum Print Area	4.0 mm from all edges		
Page Description Languages	PostScript 3 compatible PCL® 5c, 6, PDF Direct, TIFF, JPEG	PostScript 3 compatible PCL® 5c, 6, PDF Direct, TIFF, JPEG	
Print Features	Image Options (Standard, Photos, Presentation, Design, POP) Color Balance Adjust PANTONE® Color Calibrated Solid-color Simulations Auto Screening (Standard, Fineness, Gradation) Manual Duplex N-up Watermark Custom Page Sizes Fit to Page Scaling Reduce/Enlarge Draft Mode Collation Bidirectional Print Drivers Job Monitoring		
Mobile Printing	Apple® AirPrint™ Google Cloud Print Mopria® Print Service Plug-in		
Operating Systems	Microsoft® Windows® 7 (32-/64-bit), 8 (32-/64-bit), 8.1 (32-/64-bit), XP (32-/64-bit via Windows v3 driver only), 2003 Server (32-/64-bit), Windows Server 2008 (32-/64-bit), Windows Server 2012 (64-bit), Windows server 2012 R2 (64-bit), Vista (32-/64-bit) Mac OS® 10.5.8, 10.6.x, 10.7.x, 10.8.x, 10.9.x Red Hat® Enterprise Linux 6 Desktop (32-/64-bit) SUSE® Linux Enterprise Desktop 11 (32-/64-bit) Ubuntu® 12.04 (32-/64-bit)		
Network Protocols	NA	Scan to Email, Scan to SMB (SMB/SMB2 Client), Scan to FTP (FTP Client), LDAP for Address Book	
	Wired: 10/100 BaseT TCP/IP: IPsec, IPsec (IKE) / Pre-Shared Key SNMPv3 WPA_WPA_2 (Personal)_WPS_IPs/(_(including_DHCP/BOOTP/PAPP/AutoIP)_	Wired: 10/100 BaseT TCP/IP: IPsec, IPsec (IKE) / Pre-Shared Key SNMPv3, Kerberos WPA_WPA2 (Personal) WPS_IPv() (including DHCP/BOOTP/PAPP/AutoIP)	
	WPA, WPA2 (Personal), WPS, IPv4 (including DHCP/BOOTP/RARP/AutoIP), IPv4 Filter, IPv6 (including DHCPv6), IPv6:Bonjour, LPD, Port9100, IPP, IPPS, SNMPv1, SNMPv2, SNMP/UDP, SMTP/POP3, Email Alert, HTTP, HTTPS, EWS, Bonjour (mDNS), DNS, WDS (Print/Scan), SSL/TLS (with self-certificate)	WPA, WPA2 (Personal), WPS, IPv4 (including DHCP/BOOTP/RARP/AutoIP), IPv4 Filter, IPv6 (including DHCPv6), IPv6:Bonjour, LPD, Port9100, IPP, IPPS, SNMPv1, SNMPv2, SNMP/UDP, SMTP/POP3, Email Alert, HTTP, HTTPS, EWS, Bonjour (mDNS), DNS, WDS (Print/Scan), SSL/TLS (with self-certificate)	
Font Capability	81 PostScript fonts 81 PCL fonts 16 PDF fonts	81 PostScript fonts 81 PCL fonts 16 PDF fonts	

Сору	Phaser 6022	WorkCentre 6027	
Color Speed	NA		
8.5 x 11 in.		Up to 18 ppm	
A4 / 210 x 297 mm 8.5 x 14 in. / 216 x 356 mm		Up to 18 ppm Up to 14 ppm	
		Ор to 14 ppm	
Black-and-white Speed 8.5 x 11 in.		Up to 18 ppm	
A4 / 210 x 297 mm		Up to 18 ppm	
8.5 x 14 in. / 216 x 356 mm		Up to 14 ppm	
Document Scanner		Automatic Document Feeder with 15-sheet capacity	
Document Scanner Size		Up to 8.5 x 14 in. / 216 x 356 mm	
Sides (input:output)		1:1	
Quantity		1 to 99	
Resolution		Up to 600 x 600 dpi	
First-copy-out Time		As fast as 30 seconds color / 20 seconds black-and-white	
Copy Features		Reduce/Enlarge (25%–400%) Lighter/Darker Sharpness Color Balance Auto Exposure ID Card Copy Edge Erase Collate	
Scan	Phaser 6022	WorkCentre 6027	
Capability	NA	Color, Grayscale and Black-and-white Scanning	
Input Speed – Black-and-white		Scan up to 14 ipm – 8.5 x 11 in. / A4	
Input Speed – Color		Scan up to 9 ipm – 8.5 x 11 in. / A4	
Resolution (maximum)		200 dpi 300 dpi 600 dpi 1200 dpi (TWAIN only)	
Bit Depth		24-bit Color, 8-bit Grayscale, 1-bit Lineart	
Maximum Scan Area		ADF: Up to 8.5 x 14 in. / 216 x 356 mm	
Network Filing Protocol		FTP SMB/SMB2 SMTP/POP3	
File Formats		Image-only PDF TIFF JPEG	
Supported Scan Destinations		Scan to Network Computer (SMB/ FTP) Scan to Email (SMTP/POP3) WSD Application (TWAIN USB/Network), WIA (USB/WSD Scan) Mac 10.6 or later (USB/Network/Mac ICA) USB	
Scanning Solutions			
Xerox® Scan to PC Desktop Personal Edition	A desktop and server-based offering that provides document imaging, archiving, editing and organization tools Nuance PaperPort – image viewing and file management software Nuance OmniPage (for desktop/client installation) – OCR and file format conversion software Image Retriever – provides fully automated retrieval of scanned images direct from a scan enabled Xerox® WorkCentre to individual desktops.		
L	For more information, visit www.xerox.com/scan2pcSE.		

Fax	Phaser 6022	WorkCentre 6027	
Walk-up Fax4			
Fax Speed	NA	33.6 Kbps	
Memory		2 MB	
Resolution		Up to 406 x 392 dpi (Super-High Image Quality) Up to 203 x 392 dpi (Super Fine) Up to 203 x 196 dpi (High Quality) Up to 203 x 98 dpi (Standard)	
Compression		MH/MR/MMR/JBIG/ 1-bit compression	
Walk-up Fax Features		Auto Redial Auto Resend Auto Reduction One-touch dial (Up to 8) Address book (Up to 99 address entries) Group faxing (Up to 6) Delayed Start Cover page Junk Fax Filter Fax Forward (Forward, Print & Forward, Email, Email and Print, Forward to Server, Forward to Server and Print)	
Security			
Security Features	Secure HTTPS (SSL/TLS) Secure IPP SSL IP Filtering IPv6 SNMP v3 IPsec WEP(64-/128-bit) WPA2-PSK (AES) and WPA/WPA2-PSK (Mixed Mode)	Secure HTTPS (SSL/TLS) Secure IPP SSL IP Filtering IPv6 SNMP v3 IPsec WEP(64-/128-bit) WPA2-PSK (AES) and WPA/WPA2-PSK (Mixed Mode) Network Address Book Authentication (LDAP, Windows Kerberos)	
Wi-Fi Security			
	WEP(64-/128-bit) WPA2-PSK (AES) WPA/WPA2-PSK (Mixed Mode)		
Device Management			
Xerox® CentreWare® Internet Servi	ces		
Device Status	Web server embedded Tray status/contents Consumables status		
Print Queue Viewing	Visibility of current and completed jobs		
Job Submission	Print-ready files (PDF, TIFF, JPEG)	Print-ready files (PS, PCL® 5c/6, PDF, TIFF, JPEG)	
Device Administration	Allows remote installation, setting of configuration options and managemen	t of the device	
Browsers	Users can access the Embedded Web Server of the machine using a generally		
Xerox® Mobile Solutions			
Xerox® Wireless Print Solutions Adapter (Optional)	The Xerox® Wireless Print Solutions Adapter seamlessly connects your Xerox® printer or MFP to modern mobile and desktop workflows, regardless of your office environment. The Xerox® Wireless Print Solutions Adapter is your choice when: Your printer or MFP is not connected to a network but you want the ability to print from mobile devices. You need to bridge Wi-Fi connectivity with a traditional hardwire network. You want Google Cloud Print™ 2.0 (print device requires Adobe® PostScript® compatibility) or Mopria® capabilities. You want NFC tap-to-pair capabilities (requires the Xerox® Print Service Plug-in for Android). You own a Xerox® printer or MFP without embedded Apple® AirPrint™ support and want to add AirPrint compatibility (requires PostScript compatibility. The Xerox® Wireless Print Solutions Adapter's AirPrint functionality works with all Xerox® printers and MFPs that natively support AirPrint, and enables AirPrint on older Xerox® devices listed below that do not natively support AirPrint.) You want Wi-Fi Direct, which lets you connect your computer or mobile device to your printer or MFP wirelessly without the need for an access point or existing Wi-Fi network. You need performance that comes from the cutting-edge Wi-Fi 802.11ac standard, which ensures data transfer that's almost twice as fast as existing 802.11n devices. You need 256-bit encryption and advanced wireless security protocols, including WPA2™ Enterprise, HTTPS, and industry-standard 802.1X authentication. For more information, visit www.xerox.com/WPSA.		

Power Consumption	Phaser 6022		WorkCentre 6027	WorkCentre 6027	
110-127 VAC, 50/60 Hz, 7A or 220-2					
Continuous Printing (average)	340 watts 330 watts				
Standby Mode	45 watts or less		·		
Low Power Mode	10 watts or less				
Sleep Mode	3.5 watts or less				
Operating Environment					
Temperature	50° to 90°F / 10° to 32°C				
Humidity	10% to 85%				
Sound Pressure Printing Standby	49.1 dB(A) or less 21.9 dB(A) or less				
Warm-up Time (from Power Save)	Less than 35 seconds				
Dimensions and Weight (Unpackaged)	Width	Depth	Height	Weight	
Phaser 6022	15.6 in. / 397 mm	15.7 in. / 398 mm	9.7 in. / 246 mm	27.3 lb. / 12.4 kg	
WorkCentre 6027	16.2 in. / 410 mm	17.2 in. / 439 mm	15.3 in. / 388 mm	37.3 lb. / 16.9 kg	
Dimensions and Weight (Packaged)	Width	Depth	Height	Weight	
Phaser 6022	20 in. / 508 mm	19.9 in. / 505 mm	15.4 in. / 391 mm	30.4 lb. / 13.8 kg	
WorkCentre 6027	22.3 in. / 567 mm	21.3 in. / 541 mm	21 in. / 533 mm	43.9 lb. / 19.9 kg	
	Regulatory Compliance Listed to UL 60950-11/CSA 60950-1-07, 2nd Edition FCC Part 15 Class 8 FCC Part 16 S FCC Part 16 S FC				

What Comes in the Box			
Phaser 6022 Color Printer or WorkCentre 6027 Color Multifunction Printer Toner Cartridge (500 page capacity ⁵) Quick Installation Guide, Quick Use Guide, Software and Documentation Disc Power Cable USB Cable Fax Cord (WorkCentre 6027)			
Supplies and Options			
Toner Cartridges	Description	Part Number	
	Black: 2,000 standard pages⁵	106R02759	
	Cyan: 1,000 standard pages ⁵	106R02756	
	Magenta: 1,000 standard pages ⁵	106R02757	
	Yellow: 1,000 standard pages⁵	106R02758	

¹ Maximum volume capacity expected in any one month. Not expected to be sustained on a regular basis.



² Expected regular monthly throughput.

³ Paper capacities are based on 20 lb. / 75 gsm stock; capacities will vary with different weight stocks.

⁴ Requires analog phone line.

⁵ Average standard pages. Declared Yield in accordance with ISO/IEC 19798. Yield will vary based on image, area coverage and print mode.