XEROX® PRIMELINK® PRINTER

The world's #1* entry production colour printer just got even better.



C9065 CH C9070



Xerox[®] PrimeLink[®] C9065/C9070 Printer

The Xerox[®] PrimeLink[®] C9065/C9070 delivers the most adaptable capabilities on the market. From superior image quality and unmatched media flexibility to professional-grade finishing, automation and security, it takes entry level to the next level.



IMPROVE YOUR IMAGE

Entry-level price point shouldn't mean entrylevel image quality. With PrimeLink, you can deliver stunning output on every job, every time.

It all starts with resolution. 2400 x 2400 dpi means you get outstanding fine-line detail and text with vivid images and smooth colour transitions — even at speeds of up to 70 ppm. EFI servers with embedded PANTONE® technologies such as PANTONE® GOE and PANTONE® PLUS ensure the colours you want are the colours you get.

And a combination of Xerox[®] Emulsion Aggregation (EA) toner with ultra-low melt technology, +/- 1.5 mm front-to-back registration and Simple Image Quality Adjustment (SIQA) means you get consistent quality from your first print to your last.



* Idealliance, Fogra, and Adobe PDF Print Engine achieved with the optional EFI server

WORK SMARTER, NOT HARDER

Looming deadlines are the norm. Now, there's no reason to compromise. Adding a PrimeLink to your arsenal lets you upgrade your productivity in ways you wouldn't think possible.

Designed to promote multitasking and collaboration, it's customizable to suit your work style. The Xerox[®] Integrated Colour Server comes standard. Or you can choose from one of three optional EFI servers for more capabilities and more volume. All you have to do is select the best fit based on your business applications and the level of automation and colour accuracy you need.

The printer also has access to the Xerox App Gallery. With apps that connect to leading applications including Box[®], Microsoft[®] OneDrive[®], Google Drive[™], Dropbox[™] and Microsoft Office 365[™], you can print and scan directly to and from the cloud, simplify workflows and automate complex tasks.

Plus, built-in mobile connectivity with @PrintByXerox lets your team stay on-task when they're on the go. With this feature, PrimeLink can securely accept print submissions from any email-enabled device — no extra software required.

It's all there with the touch of a button. Say yes to more, and Xerox® PrimeLink C9065/C9070 will help you deliver.

SERVE AND PROTECT

PrimeLink applies a strategic approach to security to keep your network and projects safe from prying eyes. Stop suspicious activity where it starts with our comprehensive approach to security:

- Multiple layers of security include data encryption, access controls, disk overwrite and industry certifications.
- Audit Log ensures an audit trail of operators' key events. These logs are imperative for Administrators/Key Operators to use for troubleshooting, resource optimization and security audits.
- Secure Print holds documents for release until you're ready to retrieve them.
- Secure Scanning includes password protection for PDFs and folders, as well as encryption for scanning to email.

FINISH STRONG

PrimeLink delivers media latitude and finishing options that are best-in-class and unparalleled in an entry-level device.

Print on specialty stocks and heavyweight stocks up to 350 gsm. Print up to 26" (660 mm) with the Extra Long Sheet (XLS) capability up to 220 gsm. And print long runs without refilling the paper tray using high volume feeding options.

Finishing options are professional-grade, easy to navigate and nearly endless. Enjoy options ranging from full-bleed trimmed booklets to punch, crease and fold.



Xerox[®] PrimeLink[®] C9065/C9070 Printer


- **1 Two-Tray Oversized High-Capacity Feeder:** Adds 4,000 sheets in sizes from 4 x 6 in./ 100 x 148 mm to 13 x 19.2 in./330 x 488 mm (up to 350 gsm). Up to 13 x 26 in./330 x 660mm via Tray 5 (up to 220 gsm).
- 2 Extra Long Sheet (XLS) Capability: Print banners, book jackets, calendars and other applications up to 26 in. (660 mm) long, and up to 220 gsm via Tray 5 (Bypass).
- **3 Control Panel:** An intuitive user interface makes it simple to access general print, copy, scan and fax functions, integrated colour server, useful apps from the Xerox App Gallery, colour controls, security features and much more.
- **4 Integrated Scanner:** Single Pass Duplex Automatic Document Feeder scans up to 270 impressions per minute; 600 dots per inch colour up to 11 x 17/A3. Scan to a variety of output options; desktop, USB, mailbox, FTP, SFTP, SMB and Job Flow multi-destination scanning.
- 5 Xerox[®] PrimeLink[®] C9065/C9070 Printer: Prints, copies, scans and faxes all while delivering stunning colour image quality at a highly productive 65 ppm colour and 70 ppm black-and-white (C9065) or 70 ppm colour and 75 ppm black-and-white (C9070).
- **6 Five Internal Trays (Standard):** Includes a 12 x 18 in./SRA3 tray and Tray 5 (Bypass) max weight up to 350 gsm and up to 26 in./660 mm sheet size.
- 7 Xerox[®] Interface Decurler Module: Inline paper cooling and decurler unit improves throughput and efficiency connecting Production Ready finishers, ensuring flat sheets for reliability and speed.

- 8 Xerox® Inserter: Insert preprinted or blank media into printed documents with a tray capacity of 250 sheets, sheet sizes up to 13 x 19.2 in. (330 x 488 mm) and 350 gsm.
- 9 GBC[®] AdvancedPunch[™] Pro: Lets you create bound documents in-house by combining printing, punching and collating into one convenient step. Choose the punch to fit your needs.
- 10 Xerox[®] Crease and Two-Sided Trimmer: Trims 6-25 mm from the head and foot of prints or booklets to produce an even edge and creases spine. Available with Production Ready Finishers.
- **11 XEROX® C/Z FOLDER:** Produces Z-fold, C-Fold and Engineering Z-Fold.
- 12 Xerox® Production Ready Finisher Booklet: Maker: Ensures consistent high-quality stapled sets for small or large documents with a variable-length stapler, single or dual stapling option and a 100 sheet capacity. Plus, creates stapled booklets up to 30 sheets or 120 imposed pages (uncoated), or 15 sheets or 60 imposed pages (coated).
- 13 Xerox[®] SquareFold[®] Trimmer: Enhances the power of the Production Ready Finisher with square fold of cover sheets and face trimming to produce booklets.

ADDITIONAL FEEDING AND FINISHING OPTIONS NOT PICTURED

- One-Tray Xerox® High Capacity Feeder Holds 2,000 sheets of 8.5 x 11 in. (A4) paper, 64–220 gsm.
- Banner Feed Guide An option for the Tray 5 (Bypass)/MSI/OHCF that increases reliability when feeding XLS or 350 gsm media.

- One-Tray Oversized High Capacity Feeder with Storage Cabinet — Adds 2,000 sheets in sizes from 4 x 6 in. / 100 x 148 mm to 13 x 19.2 in. / 330 x 488 mm (up to 350 gsm). Up to 13 x 26 in./330 x 660 mm via Tray 5 (up to 220 gsm).
- Offset Catch Tray 500-sheet stacking.
- Xerox[®] Business Ready Finisher A lighter-duty option for finishing and stacking and staples up to 50 sheets uncoated/15 coated.
- Xerox[®] Business Ready Booklet Maker Finisher — Provides booklet making capability.
- Xerox[®] Production Ready Finisher Produces superior quality finishing and stacking with a 500-sheet top tray and 3,000-sheet stacker tray and built-in bi-directional decurler.
- Xerox® Production Ready Finisher Plus Provides same function as the Production Ready Finisher. Used to connect third-party inline finishing options
- Xerox[®] Basic Punch An option for punching 2/3, 2/4 and Swedish 4-hole on the Production Ready Finisher and Booklet Maker.
- Plockmatic Pro 50/35 Booklet Maker Highest quality production booklets up to 200 pages (up to 50 sheets). Face trimming, square fold, rotate crease and bleed trim.
- Convenience Stapler Staples up to 50 sheets of 20 lb./80 gsm media.
- Xerox® Tape Binder Combines inline thermal tape binding with the speed, value and convenience of Production printing. Connects via Xerox® Production Ready Finisher Plus
- GBC[®] eWire[™] Combines printing, punching, collating and twin- loop binding into one integrated process Runs inline with the GBC[®] AdvancedPunch[™] Pro and the Xerox[®] Production Ready Finisher Plus.



Xerox[®] PrimeLink[®] C9065 and C9070 Printer

DEVICE SPECIFICATIONS	PRIMELINK C9065			PRIMELINK C9070	
SIMPLEX SPEEDS	Colour	Black-and-white		Colour	Black-and-white
8.5 x 11 in. / A4	65 ppm	70 ppm		70 ppm	75 ppm
11 x 17 in. / A3	33 ppm	35 ppm		35 ppm	37 ppm
12 x 18 in. / SRA3	29 ppm	30 ppm		30 ppm	33 ppm
AUTO DUPLEX SPEEDS	Colour	Black-and-white		Colour	Black-and-white
8.5 x 11 in. / A4	Up to 65 ppm 2-sided 32 sheets per minute	Up to 70 ppm 2-sided 35 sheets per minute		Up to 70 ppm 2-sided 35 sheets per minute	Up to 75 ppm 2-sided 37 sheets per minute
11 x 17 in. / A3	Up to 32 ppm 2-sided 16 sheets per minute	Up to 35 ppm 2-sided 17 sheets per minute		Up to 35 ppm 2-sided 17 sheets per minute	Up to 37 ppm 2-sided 18 sheets per minute
Printer Dimensions	Height: 54.8 in. / 1,391.5 mm; Width: 62 in./ 1,574 mm; Depth: 31 in. / 787 mm				
Monthly Duty Cycle	Up to 300,000 pages (maximum volume capacity expected in any one month, not expected to be sustained on a regular basis)				
Average Monthly Print Volume	10,000 - 60,000 images per month				
(AMPV) Paper Flexibility/Weights	Standard Paper Capacity: 3,260 sheets (Tray 1 & 2: 500 sheets, Tray 3: 870 sheets, Tray 4: 1,140 sheets, Tray 5 (Bypass): 250 sheets) Max Paper Capacity: 7,260 sheets (Tray 1 & 2: 500 sheets, Tray 3: 870 sheets, Tray 4: 1,140 sheets, Oversized High Capacity Tray 1 & 2: 4,000 sheets) Sizes: Tray 1: 5.5 x 8.5 in. to 12 x 18 in. (A5 to SRA3) 5.5 x 8.5 in. to 11 x 17 in. (A5 to A3) 7.25 x 10.5 in. to 8.5 x 11 in. (B5 to A3) 7.25 x 10.5 in. to 8.5 x 11 in. (A5 to A4)				
Image Quality Print Technology	Benchmark image quality with 2400 x 2400	dpi resolution with VCSEI	ROS and EA Eco wit	n ultra-low melt technology toner for a sma	oth, offset-like finish
Line Screens	150/200/300/600 dot screen, 200 line screen, stochastic and enhanced text and graphics				
Registration	 Advanced registration technology for tighter control Simple Image Quality Adjustment (SIQA) for de-skew, registration and density uniformity (available on all configurations) +/- 1.5 mm. Variation will occur based on paper size, tray, etc., 				
Print Features	 Print, copy, fax and scan, including Scc USB or Email, and mobile printing Expansive media range lets you print to posters, both coated and uncoated Xerox Extensible Interface Platform[®] connect to third-party software soluti Inline finishing options offer a profess banner printing, stapling, hole-punchi- making for presentations, brochures, r Be secure with integrated security fea IP filtering, image overwrite, secure pr 	everything from postca I stock, up to 350 gsm (EIP) allows you to ons sional polish with ing, folding and booklet reports and newsletters itures such as int, encrypted	 XLS sheet size (Tray 5 and OHCF via Tray 5) supporting up to 220gsm Up to 350 gsm (Tray 5 and OHCF only), auto-duplex up to 256 gsm (Bypass Tray and OHCF) Xerox® replaceable units for toners, drums, fuser, charge corotron, waste bottle, staples Custom Paper Setup and Paper Catalog Load-while-run toner and paper capability Optional Features: Common Access Card Enablement Kit, Accounting Options, Foreign Device Interface 		
	Scan to Email, authentication and IPv				
Servers Integrated Scanner	Standard Xerox® Integrated Colour Server Single-pass Dupley Automatic Docum	•	 Optional Xerox[®] Optional Xerox[®] 	EX C9065 Series Print Server Powered by EX C9065 Series Print Server Powered by EX C9065 Series Print Server Powered by	/ Fiery®
-	 Colour or black-and-white scanner Scan to text searchable PDF, PDF/A, th XPS[®], PCL[®] 6, HP-GL2 (direct submission) 250-sheet capacity 	numbnail preview, on), TIFF, JPEG	Up to 270 ipm (colour, up to 200 gsm) Up to 270 ipm (black-and-white, up to 200 gsm) Originals up to 11 x 17 in. (A3) in weights from 38 gsm (16 lb. bond) to 200 gsm (53 lb. bond) 1 in (184 2 x 266 7 mm to 220 x 688 mm);		
Optional Feeding	High Capacity Feeder (HCF) 2,000 sheets - 7.25 x 10.5 in. to 8.5 x 11 in. (184.2 x 266.7 mm to 330 x 488 mm); 16 lb. bond to 60 lb. cover (64 to 220 gsm). Optional Oversized High Capacity Feeder (OHCF): One-Tray OHCF: 2,000 sheets plus Storage Cabinet; Tray 6: 3.9 x 5.8 in. / 100 x 148 mm to 13 x 19.2 in. / 330 x 488 mm (up to 350 gsm) Tray 5: Up to 13 x 26 in./330 x 660 mm (up to 220 gsm). Two-Tray OHCF: 4,000 sheets; OHCF: Tray 67: 3.9 x 5.8 in. / 100 x 148 mm to 13 x 19.2 in./ 330 x 488 mm (up to 350 gsm) Tray 5: Up to 13 x 26 in./330 x 660 mm (up to 220 gsm).				
Optional Finishing	 Business Ready Finisher: Offsetting Top Tray: 500-sheets 8.5 x 11 in. / A4 unstapled. Stacking Stapling Tray: 3,000 sheets unstapled or 100 sets (dual or 4-position staple) 1x17 in., 8.5 x 14 in., A3 or 200 sets (single-position staple) 8.5 x 11 in. / A4. Sizes: Letter (4 x 6 in.), A4 (12 x 19.2 in.), JIS SRA3 (7.25 x 10.5 in.), Executive (11 x 17 in.) Other; 5.5 x 8.5 in. / A5 output to top tray; punch and offset. Paper Weights: Top Tray: 16 lb. bond to 130 lb. cover / 60 to 350 gsm (coated and uncoated). Business Ready Finisher Booklet Maker Finisher: Offsetting Top Tray: 500-sheets 8.5 x 11 in. / A4 unstapled. Stacking Stapling Tray: 1,500 sheets unstapled or 200 sets (single-position staple) or 100 stapled sets of 11 x 17 in. / A3 / SRA3. 11x17 in., 8.5 x 14 in., A3 or 200 sets (single-position staple) 8.5 x 11 in. / A4. Sizes: 4 x 6 in, to 12 x 19.2 in. (A6 to SRA3) 7.25 x 10.5 in. to 11 x 17 in. (B5 to A3) Other; 55 x 8.5 in. / A5 output to top tray; punch and offset. Paper Weights: Top Tray: 10 bend to 96 lb. cover / 60 to 350 gsm (coated and uncoated). Booklet Maker-Saddle-stitch 2 to 16 sheets (7 sheets at 106 to 176 gsm coated or 5 sheets at 107 to 220 gsm (coated). Booklet Maker-Saddle-stitch 2 to 16 sheets (7 sheets at 106 to 176 gsm coated or 5 sheets at 107 to 220 gsm (coated). Booklet Maker-Saddle-stitch 2 to 16 sheets (17 sheets at 106 to 176 gsm coated or 5 sheets at 107 to 220 gsm (coated). Production Ready Finisher Weight: 7330 x 488mm. Production Ready Finisher Plus (requires Interface Decurler Module): Provides same function as the Xerox® Production Ready Finisher with a 500-sheet top tray, sa00-sheet top tray and 2,000-sheet stack tray (J00.5heet stack fray, saddle-stitch booklet Maker (requires Interface Decurler Module): Booklet Size: 7.17 x 7.17" (182 x 182mm) to 13 x 19.2" (330 x 488mm) Tray: 500-sheet tack ray. J000-sheet stack tray, saddle-stitch booklet tray (up to 120 pages, 30 sheets/90 gsm uncoated,				
	Xerox® SquareFold® Trimmer Module Fa Xerox® C/Z Folder Sheet Size: 8.5 x 11" (A4 Finisher, Booklet Maker. Xerox® Inserter Capacity: 250 sheets. Cap 13" x 19.2" (330 x 488 mm) Max Weight: 75 11 Xerox® Crease and Two-Sided Trimm 75350 gsm. Compatibility: Production Read	i). Half-Z Fold Sheet Size: babilities: Trimming, pund 5350 gsm. Compatibility: ner Trim Range: 0.236" (f dy Finisher and Booklet M	Larger stocks reducir ching, folding, staplir Production Ready Fi 5 mm) to 0.985" (25 r laker. Buffering Unit	ng to 8.5 x 11" (A4). Weight Range: 6490 g Ig, stacking. Paper Size: 7.2" x 5.8" (182 x 1 nisher. mm). Paper Size: 7.7" x 8.3" (194 x 210 mm : Up to five customizable mountain or valle	sm. Compatibility: Production Ready 48 mm) to) to 13" x 19.2" (330 x 488 mm) 29 creases per sheet.
	Xerox® SquareFold® Trimmer Module Fa Xerox® C/Z Folder Sheet Size: 8.5 x 11" (A4 Finisher, Booklet Maker. Xerox® Inserter Capacity: 250 sheets. Cap 13" x 19.2" (330 x 488 mm) Max Weight: 75 11 Xerox® Crease and Two-Sided Trimm 75350 gsm. Compatibility: Production Read	abilities: Trimming, punk s350 gsm. Compatibility: ner Trim Range: 0.236" (f dy Finisher and Booklet N ooklet Capacity: 200 pag w Weight: 75300 gsm. Co	Larger stocks reduci ching, folding, staplir Production Ready Fi 5 mm) to 0.985" (25 r Iaker, Buffering Unit ges (50 sheets). Capc mpatibility: Producti	ng to 8.5 x 11" (A4). Weight Range: 6490 g ig, stacking. Paper Size: 7.2" x 5.8" (182 x 1 nisher. mm). Paper Size: 7.7" x 8.3" (194 x 210 mm Up to five customizable mountain or valla abilities: Face trimming, square fold, rotate ion Ready Finisher Plus.	sm. Compatibility: Production Ready 48 mm) to) to 13" x 19.2" (330 x 488 mm) 2y creases per sheet. 2 crease and bleed trim.

Configurations vary by geographical location.

For more information, go to https://www.xerox.ca/en-ca/digital-printing/insights/professional-colour-printer.

Xelox[™]

© 2020 Xerox Corporation. All rights reserved. Xerox®, PrimeLink®, and Squarefold® are trademarks of Xerox Corporation in the United States and/or other countries. The information in this brochure is subject to change without notice. 11/20 TSK-678 BR26905 PC9BR-01CD