

# Xerox® VersaLink® Multifunction Printer

B7025/B7030/B7035



VersaLink B7000 Series Multifunction Printers are built on Xerox® ConnectKey® Technology. For more information, go to [www.connectkey.com](http://www.connectkey.com).

System Specifications	VersaLink B7025	VersaLink B7030	VersaLink B7035
<b>One-Sided Speed</b> 8.5 x 11 in. / A4 / 210 x 297 mm 8.5 x 14 in. / 216 x 356 mm 11 x 17 in. / A3 / 297 x 420 mm	Up to 25 ppm (pages per minute) long edge feed (LEF) Up to 16 ppm 8.5 x 14 in. / 216 x 356 mm Up to 14 ppm 11 x 17 in. / A3 / 297 x 420 mm	Up to 30 ppm (LEF) Up to 20 ppm 8.5 x 14 in. / 216 x 356 mm Up to 17 ppm 11 x 17 in. / A3 / 297 x 420 mm	Up to 35 ppm (LEF) Up to 22 ppm 8.5 x 14 in. / 216 x 356 mm Up to 19 ppm 11 x 17 in. / A3 / 297 x 420 mm
<b>Monthly Duty Cycle<sup>1</sup></b>	Up to 107,000 pages / month <sup>1</sup>	Up to 129,000 pages / month <sup>1</sup>	Up to 153,000 pages / month <sup>1</sup>
<b>Recommended Average Monthly Print Volume<sup>2</sup></b>	Up to 13,000 pages	Up to 15,000 pages	Up to 17,000 pages
<b>Hard Drive</b>	320 GB HDD		
<b>Processor</b>	1.05 GHz Dual-Core		
<b>Memory</b>	2 GB		
<b>Connectivity</b>	Ethernet 10/100/1000 Base-T, High-speed USB 3.0, Wi-Fi 802.11n and Wi-Fi Direct with optional Wi-Fi Kit (concurrent wired and wireless connections supported), NFC Tap-to-Pair		
<b>Controller Features</b>	Unified Address Book, Configuration Cloning, Scan Preview, Xerox Extensible Interface Platform®, Xerox App Gallery, Xerox® Standard Accounting, Role Based Permissions, Convenience Authentication Enabled, Online Support		
<b>Device Specifications</b>			
<b>Electrical Requirements</b>			
North America	Voltage : 110-127V -10% / +6% Frequency: 50/60 Hz +/-3%, 12A		
Europe	Voltage : 220-240V +/- 10% Frequency: 50 Hz +/-3%, 8A		

# Xerox® VersaLink® B7025/B7030/B7035 Multifunction Printer

Power Consumption				
Printing <sup>4</sup>	For 110V: 25 ppm = 1.1 kWh; 30 ppm = 1.5 kWh; 35 ppm = 1.7 kWh For 220V: 25 ppm = 1.1 kWh; 30 ppm = 1.5 kWh; 35 ppm = 1.8 kWh			
Standby Mode <sup>4</sup>	110V: 83 Watts or less; For 220V: 86 Watts or less			
Sleep Mode <sup>4</sup>	110V: 1.2 watts or less, 220V: 1.4 watts or less			
Operating Environment				
Required Temperature Range (Storage)	32° to 95° F (0° to 35° C)			
Required Temperature Range (Operating)	50 to 90° F (10 to 32° C)			
Required Relative Humidity	10% to 85%			
Sound Power Levels	Printing: 6.75 B(A) or less • 25 ppm = 6.54 B(A); 30 ppm = 6.70 B(A); 35 ppm = 6.75 B(A) Standby: 4.10 B(A) or less • 25 ppm = 4.10 B(A); 30 ppm = 4.10 B(A); 35 ppm = 4.10 B(A)  <b>Full System (including finisher and HCF)</b> Printing: 25 ppm = 7.22 B(A); 30 ppm = 7.37 B(A); 35 ppm = 7.46 B(A) Standby: 25 ppm = 6.54 B(A); 30 ppm = 6.70 B(A); 35 ppm = 6.75 B(A)			
Sound Pressure Levels	Printing: 50.0 dB(A) • 25 ppm = 49.4 dB(A); 30 ppm = 49.7 dB(A); 35 ppm = 50.0 dB(A) Standby: 16.4 dB(A) • 25 ppm = 16.4 dB(A); 30 ppm = 16.4 dB(A); 35 ppm = 16.0 dB(A)  <b>Full System (including finisher and HCF)</b> Printing: 25 ppm = 53.4 dB(A); 30 ppm = 53.6 dB(A); 35 ppm = 54.0 dB(A) Standby: 25 ppm = 16.0 dB(A); 30 ppm = 16.0 dB(A); 35 ppm = 15.7 dB(A)			
Boot Time (from Off to UI Ready)	As fast as 98 seconds			
Warm-up Time (from Sleep to UI Ready)	As fast as 12 seconds			
Dimensions and Weight (Unpackaged)	Width	Depth	Height	Weight
Base Unit with Single Tray with Stand Module	24.24 in. / 615.7 mm	26.41 in. / 670.8 mm	44.04 in. / 1118.6 mm	168.21 lbs. / 75.8 kg
Base Unit with High Capacity Tandem Tray Unit	24.24 in. / 615.7 mm	26.41 in. / 670.8 mm	44.04 in. / 1118.6 mm	193.35 lbs. / 87.2 kg
With Office Finisher LX (with Booklet Maker)	47.0 in. / 1194.0 mm	26.8 in. / 681.8 mm	44.04 in. / 1118.6 mm	249.12 lbs. / 113.0 kg
Certifications				
	To view the latest list of certifications, go to <a href="http://www.xerox.com/OfficeCertifications">www.xerox.com/OfficeCertifications</a> .			
Paper Handling				
Document Feeder				
Capacity <sup>3</sup>	Duplex Automatic Document Feeder (DADF): 110 sheets			
Sizes	Custom sizes: Duplex: 4.92 x 4.33 in. to 11.69 x 17 in. / 125 x 110 mm to 297 x 431.8 mm; Simplex: 4.92 x 3.35 in. to 11.69 x 17 in. / 125 x 85 mm to 297 x 431.8 mm			
Weights	Simplex: 11 lb. bond to 34 lb. bond / 38 to 128 gsm Duplex: 13 lb. bond to 34 lb. bond / 50 to 128 gsm			
Bypass Tray				
Capacity <sup>3</sup>	100 sheets			
Sizes	Custom sizes: 3.5 x 3.87 in. to 11.69 x 17 in. / 88.9 x 98.4 mm to 297 x 431.8 mm			

## Xerox® VersaLink® B7025/B7030/B7035 Multifunction Printer

<b>Weights</b>	16 lb. bond to 80 lb. cover / 60 to 216 gsm
<b>Types</b>	Bond Plain Paper Cardstock Custom Envelopes Hole Punched Labels Heavyweight Labels Letterhead Lightweight Cardstock Pre-Printed Recycled
<b>Tray 1</b>	
<b>Capacity<sup>3</sup></b>	520 sheets
<b>Sizes</b>	Custom sizes: 5.5 x 7.17 in. to 11.69 x 17 in. / 139.7 x 182.0 mm to 297.0 x 431.8 mm
<b>Weights</b>	16 lb. bond to 95 lb. cover / 60 to 256 gsm
<b>Types</b>	Bond Plain Paper Cardstock Custom Hole Punched Labels Heavyweight Labels Extra Heavyweight Labels Letterhead Lightweight Cardstock Heavyweight Cardstock Pre-Printed Recycled
<b>Single Tray Module with Stand (Optional)</b>	
<b>Capacity<sup>3</sup></b>	520 sheets
<b>Sizes</b>	Custom sizes: 5.5 x 7.17 in. to 11.69 x 17 in. / 139.7 x 182.0 mm to 297.0 x 431.8 mm
<b>Weights</b>	16 lb. bond to 95 lb. cover / 60 to 256 gsm
<b>Types</b>	Bond Plain Paper Cardstock Custom Hole Punched Labels Heavyweight Labels Extra Heavyweight Labels Letterhead Lightweight Cardstock Heavyweight Cardstock Pre-Printed Recycled
<b>High Capacity Tandem Tray Module (Optional)</b>	
<b>Capacity<sup>3</sup></b>	Tray 2: 520 sheets Tray 3: 870 sheets Tray 4: 1,130 sheets
<b>Sizes</b>	Tray 2: Custom sizes: 5.5 x 7.17 in. to 11.69 x 17 in. / 139.7 x 182.0 mm to 297.0 x 431.8 mm Tray 3: Standard Sizes: 8.5 x 11 in. and 7.25 x 10.5 in. / A4 or B5 Tray 4: Standard Sizes: 8.5 x 11 in. and 7.25 x 10.5 in. / A4 or B5
<b>Weights</b>	16 lb. bond to 95 lb. cover / 60 to 256 gsm
<b>Types</b>	Bond

## Xerox® VersaLink® B7025/B7030/B7035 Multifunction Printer

	Plain Paper Cardstock Custom Hole Punched Labels Heavyweight Labels Extra Heavyweight Labels Letterhead Lightweight Cardstock Heavyweight Cardstock Pre-Printed Recycled
<b>Envelope Tray – Replaces Tray 1 (Optional)</b>	
<b>Capacity<sup>3</sup></b>	Up to 60 envelopes
<b>Sizes</b>	#10 commercial, Monarch, DL, C5 Custom sizes: 3.9 x 5.8 in. to 6.4 x 9.5 in. / 98 x 148 mm to 162 x 241 mm
<b>Weights</b>	20 lb. bond to 25 lb. bond / 75 to 90 gsm
<b>High Capacity Feeder (Optional)</b>	
<b>Capacity<sup>3</sup></b>	2,000 sheets
<b>Sizes</b>	Standard Sizes: 8.5 x 11 in. and 7.25 x 10.5 in. / A4 or B5
<b>Weights</b>	16 lb. bond to 80 lb. cover / 60 to 216 gsm
<b>Total Capacity</b>	
<b>Base Unit with Single Tray Module with Stand Capacity<sup>3</sup></b>	1,140 sheets
<b>Base Unit with High-Capacity Tandem Tray Capacity<sup>3</sup></b>	3,140 sheets
<b>Finishing</b>	
<b>Output Trays</b>	
<b>Dual Catch Trays<sup>3</sup></b>	250 sheets each; Lower tray offsets
<b>Integrated Office Finisher (Optional)</b>	
<b>Stacking Tray</b>	500 sheets of 20 lb. bond / 80 gsm – 8.5 x 11 in. / A4 or 250 sheets of 20 lb. bond / 80 gsm – 11 x 17 in. / A3
<b>Sizes</b>	3.5 x 3.9 in. to 11.7 x 17 in. / 89 x 98 mm to 297 x 432 mm
<b>Weights</b>	16 lb. bond to 80 lb. cover / 60 to 220 gsm
<b>Stapling</b>	Single Auto stapling: 50 sheets maximum: Letter / A4 / B5-size sheets (less than 90 gsm or (2) 220 gsm covers) 30 sheets maximum: Legal / Tabloid / A3 / B4-size sheets (less than 90 gsm or (2) 220 gsm covers)
<b>Office Finisher LX (Optional)</b>	
<b>Capacity<sup>3</sup></b>	Stacking Tray: 2,000 sheets unstapled or 1,000 sheets single stapled or 750 sheets dual stapled (8.5 x 11 in. / A4) (dual stapling only with optional booklet maker)
<b>Sizes</b>	8.3 x 7.2 in. to 11.7 x 17 in. / 210 x 182 mm to 297 x 432 mm
<b>Weights</b>	16 lb. bond to 80 lb. cover / 60 to 220 gsm
<b>Multiposition Stapling</b>	50 sheets of 24 lb. bond / 90 gsm
<b>Hole Punch (Optional)</b> <b>North America:</b> <b>Europe:</b>	2-3 Hole Punch 2-4 Hole Punch
<b>Booklet Maker for Office Finisher LX (Score/Crease, Saddle-stitch Staple) (Optional)</b>	
<b>Capacity<sup>3</sup></b>	40 booklets (2-15 sheets per booklet – 20 lb. / 80 gsm or less)

# Xerox® VersaLink® B7025/B7030/B7035 Multifunction Printer

<b>Sizes</b>	Letter – 8.5 x 11 in. / A4 SEF Legal – 8.5 x 14 in. / B4 SEF Ledger – 11 x 17 in. / A3 SEF		
<b>Saddle-stitch Stapling</b>	2-15 sheets / 8-60 page booklet 16 lb. bond to 24 lb. bond / 60 to 90 gsm		
<b>Score / Crease</b>	1-15 sheets / unstapled		
<b>Convenience Stapler and Work Surface (Optional)</b>			
<b>Capacity<sup>3</sup></b>	50-sheet stapling 5,000 staples Requires a separate outlet		
<b>Copy</b>			
<b>Document Scanner</b>	110-sheet Duplex Automatic Document Feeder (DADF)		
<b>Document Scanner Size</b>	Platen: Up to 13.1 x 17.2 in. / 332.0 x 437 mm DADF: Up to 11.7 x 17 in. / 297 x 431.8 mm		
<b>Simplex Copy Speed</b>	Up to 25 cpm (copies per minute) 8.5 x 11 in. Up to 25 cpm A4 (210 x 297 mm)	Up to 30 cpm (copies per minute) 8.5 x 11 in. Up to 30 cpm A4 (210 x 297 mm)	Up to 35 cpm (copies per minute) 8.5 x 11 in. Up to 35 cpm A4 (210 x 297 mm)
<b>Duplex Copy Speed</b>	Up to 20 cpm (copies per minute) 8.5 x 11 in. Up to 20 cpm A4 (210 x 297 mm)	Up to 20 cpm (copies per minute) 8.5 x 11 in. Up to 20 cpm A4 (210 x 297 mm)	Up to 20 cpm (copies per minute) 8.5 x 11 in. Up to 20 cpm A4 (210 x 297 mm)
<b>First-copy-out Time</b>	As fast as 6.8 seconds	As fast as 5.4 seconds	As fast as 5.4 seconds
<b>Sides (input:output)</b>	1:1, 1:2, 2:2 and 2:1		
<b>Quantity</b>	1 to 999		
<b>Resolution (max.)</b>	Up to 600 x 600 dpi		
<b>Reduction / Enlargement</b>	Variable zoom from 25 % to 400 % in 1 % increments		
<b>Concurrency</b>	Concurrent scanning and printing		
<b>Copy Features</b>	Annotations (Page Numbers, Comments, Date Stamp, Bates Stamp) Automatic Background Suppression Book Copying with Center Erase Booklet Creation Collation Darkness Control Edge Erase ID Card Copy N-up Reduce / Enlarge 25 % to 400 % Image Shift Original Type Sample Copy Sharpness		
<b>Print</b>			
<b>First-print-out Time</b>	As fast as 10.4 seconds	As fast as 9.1 seconds	As fast as 9.1 seconds
<b>Print Resolution</b>	Up to 1200 x 1200 dpi		
<b>Page Description Languages</b>	PCL® 5e, 6 PDF XPS TIFF JPEG HP-GL Adobe® PostScript® 3™ (Optional)		
<b>Maximum Print Area</b>	4 mm from lead edge of paper, 2 mm from Side and Trail edges of paper		
<b>Print Features</b>	Application Defaults Bi-directional Real-time Status		

## Xerox® VersaLink® B7025/B7030/B7035 Multifunction Printer

	<p>Booklet Creation  Draft Mode  Job Identification  Job Monitoring  Personal Print  Print from USB  Sample Set  Saved Job  Scaling  Secure Print  Skip Blank Pages  Store and Recall Driver Settings  Two-sided Printing (as default)  Xerox® Earth Smart Driver Settings</p>
<b>Print from USB</b>	<p>Allows walk-up printing from Type A USB port  Supports direct printing from computer via Type B USB port  Supported file formats: PDF, JPEG, TIFF, XPS</p>
<b>Operating Systems</b>	<p>Windows®, 7, 8, 10, Server 2000, Server 2003, Server 2008, Server 2008 R2 Server 2012  Mac OS® version 10.10, 10.11, &amp; 10.12  Citrix  Redhat® Enterprise  Linux®  IBM® AIX® 7.2  HP-UX® 11iv3  Oracle® Solaris 11.3  Fedora Core 24  SUSE® 13.2</p>
<b>Network Protocols</b>	<p>TCP/IP: HTTP/HTTPS, Internet Printing Protocol, LPR/LPD, Raw Socket Printing/Port 9100, IPv4/IPv6,  WSD  LDAP  Bonjour® / AirPrint™  FTP  Most protocols not in use can be disabled</p>
<b>Administrative Protocols</b>	<p>DHCP, SNMP, WINS, HTTP, HTTPS, TLS, SNTP, MDNS</p>
<b>Fonts</b>	<p>PostScript fonts: 136  PCL fonts: 83</p>
<b>Mobile Solutions and Mobile Device Apps</b>	
<b>Xerox® Mobile Express Driver®</b>	<p>Makes it easy for mobile users to find, use and manage Xerox® and non-Xerox® devices in every new location. Plug into a new network, and Mobile Express Driver automatically discovers available printers and provides status and capability information. Save a list of “favorite” printers for each location, store application print settings for use on any printer in any network, and greatly reduce mobile support calls to IT.</p>
<b>Xerox® Global Print Driver®</b>	<p>A truly universal print driver that lets IT administrators install, upgrade and manage Xerox® and non-Xerox® devices from a single driver. It provides a consistent, easy-to-use interface for end-users, reducing the number of support calls, and simplifying print services management.</p>
<b>Apple® AirPrint®</b>	<p>Print email, photos and important office documents directly from an Apple iPhone® or iPad® with no drivers to install and no cables to connect. With AirPrint, an iPhone or iPad automatically locates and connects to the AirPrint-enabled device over the office Wi-Fi network.</p>
<b>Google Cloud Print™</b>	<p>Google Cloud Print connects print devices to the web, enabling users to print the applications they use every day from smartphones, tablets, Chromebook™ notebook computers and any other web-connected device.</p>
<b>Xerox® Print Service Plug-in for Android™ (Free at Google Play™ Store)</b>	<p>The Xerox® Print Service Plug-in for Android KitKat (4.4 or greater) devices streamlines mobile printing without third-party apps or additional print drivers. You can easily print photos, Web pages and documents when your mobile device is connected to multifunction printers using a wireless network. A robust print option set includes two-sided printing, stapling and secure code release. A free download is available from the Google Play™ store.</p>
<b>Xerox® Mobile Link App (Free at Google Play™)</b>	<p>The Xerox® Mobile Link App allows you to scan, email and fax from your phone or tablet by connecting with our multifunction printers and send data to and print data from cloud storage. It is easy to create</p>

## Xerox® VersaLink® B7025/B7030/B7035 Multifunction Printer

<b>Store and Apple® App Store)</b>	Mobile Link One-Touch Workflows between a mobile device and a multifunction printer. Using a manual address or QR code identification for pairing, automatic device discovery makes it easy to find and pair a mobile device with a nearby Xerox® multifunction printer.
<b>Xerox® Print Management and Mobility Suite, Xerox® Print Management and Mobility Service</b>	Xerox® Print Management and Mobility Suite is a modular set of workflows designed to save customers time and money by providing effective control over their print fleet, while enabling worker productivity and mobility through a set of robust workflows. Xerox enables ultimate customer flexibility by offering these capabilities in both an on-premises server version and with a cloud based-version of this solution.
<b>Scan</b>	
<b>Capability</b>	Black-and-white and color scanning
<b>Concurrency</b>	Scan while the system is printing copy or network print jobs, or while it is transferring scan to network or fax jobs
<b>Simplex Input Speed</b>	Black-and-white: Scan up to 55 ipm – 8.5 x 11 in. / A4 (210 x 297 mm) Color: Scan up to 55 ipm – 8.5 x 11 in. / 55 ipm A4 (210 x 297 mm)
<b>Duplex Input Speed</b>	Black-and-white: Scan up to 26 ipm – 8.5 x 11 in. / A4 (210 x 297 mm) Color: Scan up to 26 ipm – 8.5 x 11 in. / 26 ipm A4 (210 x 297 mm)
<b>Resolution</b>	Optical – 600 x 600 dpi
<b>Bit Depth</b>	24-bit color / 8-bit grayscale
<b>Maximum Scan Area</b>	Platen: Up to 13.1 x 17.2 in. / 332 x 437 mm Document Feeder: 11.7 x 17 in. / 297 x 431.8 mm
<b>Network Filing Protocols</b>	FTP SMTP SMB
<b>File Formats</b>	JPG TIFF (single and multi-page) XPS (single and multi-page) PDF (single and multi-page) Searchable PDF Password-protected PDF Linearized PDF (set via embedded web server) and PDF/A
<b>Scan Driver Compatibility (Network Only)</b>	WIA TWAIN
<b>Supported Scan Destinations</b>	Scan to Home Scan to USB Scan to Email Scan to Network (Browse FTP or Browse SMB)
<b>Network Scanning – Software Solutions</b>	
<b>Xerox® ConnectKey® Apps (Found at the Xerox® App Gallery)</b>	Increase user productivity by simplifying and shortening everyday tasks. Unlike traditional software, ConnectKey Apps do not require a dedicated server, PC or IT resource. Instead, simply download these lightweight, serverless ConnectKey Apps to the ConnectKey-enabled multifunction printer.
<b>Security</b>	
<b>Standard Security Features</b>	Firmware Verification Security Certificate Management Automatic Self-Signed Certificate Creation Certificate Revocation List (CRL)/Online Certificate Status Protocol (OCSP) Certificate Path Validation Immediate Disk Overwrite AES 256-bit Encryption FIPS 140-2 TLS/SSL SNMPv3 Smart Card Enablement (CAC/PIV.NET) Detection of external program falsification (XCP Plug-in) Network Authentication Access Controls Role Based Permissions

## Xerox® VersaLink® B7025/B7030/B7035 Multifunction Printer

	Domain Filtering IP Address Filtering Port Filtering Audit Log Secure Email Secure Fax Secure Print Secure Scan
<b>PSTN One-line or Three-line Fax (optional)</b>	
<b>Fax<sup>5</sup></b>	
<b>Fax Speed</b>	33.6 Kbps
<b>Resolution</b>	Up to 600 x 600 dpi resolution
<b>Compression</b>	MH, MR, MMR, JBIG
<b>Fax Features</b>	Walk-up Fax, includes LAN Fax, Direct Fax, Fax Forward to Email Fax dialing via Unified Address Book (up to 2,000 contacts)
<b>Fax over IP (optional)</b>	
<b>Compliance</b>	T.38 compliant IP / SIP
<b>Resolution</b>	Up to 600 x 600 dpi resolution
<b>Compression</b>	MH, MR, MMR, JBIG
<b>Fax Features</b>	Walk-up Fax, includes LAN Fax, Direct Fax, Fax Forward to Email Fax dialing via Unified Address Book (up to 2,000 contacts)
<b>Device Management</b>	
<b>Xerox® CentreWare® Web</b>	
	<ul style="list-style-type: none"> <li>• A Web-based server application for network administrators that permits web browser-based device management from any workstation, whether running Windows or UNIX or any other operating system</li> <li>• Works with any SNMP-managed printer from any manufacturer</li> <li>• Provides help with device discovery and installations, health checks and troubleshooting, and device upgrades, as well as basic accounting and asset management</li> </ul>
<b>Xerox® Embedded Web Server – Integrated Device Web Page</b>	
<b>Device Status</b>	<ul style="list-style-type: none"> <li>• Tray status/contents</li> <li>• Consumables status</li> <li>• Billing/Usage</li> <li>• Quick Links</li> </ul>
<b>Print Queue Viewing</b>	Job print queue management—View and delete
<b>Job Submission</b>	Print-ready files (PS, PCL, PDF, XPS, JPEG)
<b>Device Administration</b>	Allows simple, remote installation setting of configuration options and management of the device
<b>Browsers</b>	Microsoft® Internet Explorer® 11 Microsoft Edge™ 38 Mozilla™ Firefox® 48 Apple® Safari® 9.1 Google Chrome™ 52
<b>Remote Services</b>	
<b>Xerox® Meter Assistant® Service</b>	Automates the process of collecting and submitting meter reads for tracking and billing of Xerox® device usage. Eliminates the need for time-consuming end-user involvement and ensures that meter reads are submitted to Xerox on time.
<b>Xerox® Supplies Assistant® Service</b>	Automatically orders supplies for Xerox® output devices based on actual usage, eliminating the need to manually manage supplies inventory.



## Xerox® VersaLink® B7025/B7030/B7035 Multifunction Printer

<b>MaintenanceAssistant</b>	Offers a fast (and free) way to resolve potential issues and receive assistance and automate the troubleshooting/repair process. Diagnostic data is sent to Xerox, allowing for problems to be solved faster with increased uptime.	
<b>Accounting</b>		
<b>Xerox® Standard Accounting / Network Accounting (Standard)</b>		
<b>Tracking</b>	Copy, Print, Fax, Scan and Email usage	
<b>Accounting</b>	Up to 30,000 User Accounts  <b>Network Accounting (Job Based Accounting)</b> Up to 1,000 User IDs; Up to 1,000 Account IDs Up to 14,000 accounting records (transactions)	
<b>Features</b>	Administrator can manage the feature via the Embedded Web Server or local user interface on device	
<b>Accounting Options – Network Accounting (Allows central server to manage all accounting)</b>		
	<ul style="list-style-type: none"> <li>• Enhanced network accounting with up to the minute data on how the system is being used</li> <li>• Comprehensive management and enterprise scale tracking and reporting of device usage of copy, print, scan and fax</li> <li>• Numerous solutions are available through Xerox Alliance Partners. For details visit <a href="http://www.xerox.com">www.xerox.com</a></li> <li>• Security enhancements includes support for HTTPS protocol</li> <li>• Device requests account authentication from third party server enabling larger databases of users and accounts</li> <li>• Accept Authentication Login at control panel and pass to third party Networking Account</li> </ul>	
<b>Supplies and Accessories</b>	<b>Quantity</b>	<b>Part Number</b>
<b>Supplies</b>		
Standard Capacity Print Cartridges	15,500 standard pages <sup>6</sup>	106R03393
High Capacity Print Cartridges	31,000 standard pages <sup>6</sup>	106R03394
Worldwide Metered Print Cartridge	30,000 standard pages <sup>7</sup>	106R03392
Black Drum Cartridge	80,000 pages <sup>8</sup>	113R00779
LX Booklet Maker Cartridge (8 cartridges per carton)	16,000 staples	008R12897
Staple Refills for Finishers (3 cartridges per carton)	15,000 staples	008R12941
Staple Cartridge for Finishers (1 cartridge per carton)	5,000 staples	008R12964
<b>Accessories / Options</b>		
Envelope Tray (This replaces Tray 1)		497K17720
1 Line Fax Kit (PSTN Fax)		497K17750
3 Line Fax Kit (PSTN Fax)		497K17760
Wireless Network Adapter Kit		497K16750
Internal Card Reader / RFID Kit		497K18120 (WH)
PostScript Kit		497K17810
Fax Over IP Kit		497K17820

# Xerox® VersaLink® B7025/B7030/B7035 Multifunction Printer

<sup>1</sup> Maximum volume capacity expected in any one month. Not expected to be sustained on a regular basis.

<sup>2</sup> Expected regular monthly throughput.

<sup>3</sup> Paper capacities are based on 20 lb. / 75 gsm stock; capacities will vary with different weight stocks.

<sup>4</sup> Power states defined per ENERGY STAR® Program requirements for Imaging Equipment.

<sup>5</sup> Requires analog phone line.

<sup>6</sup> Average standard pages. Declared Yield in accordance with ISO/IEC19752. Yield will vary based on image, area coverage and print mode.

<sup>7</sup> Assumptions: Toner cartridge yield is based on 5% area coverage on 8.5 x 11 in. / A4 LEF. Toner yield can vary due to many factors, including but not limited to, image area coverage, image content, media size, run mode, application types, monthly print volumes and image quality set-points.

<sup>8</sup> Approximate pages. Declared yield will vary depending on job run length and media size/orientation and machine speed.

Return spent imaging supplies through the Xerox Green World Alliance collection/reuse/recycling program. For more information, visit [www.xerox.com/about-xerox/recycling](http://www.xerox.com/about-xerox/recycling).

For more information, visit us at [www.xerox.com/office](http://www.xerox.com/office)

Configurations vary by geography.