

# Xerox<sup>®</sup> VersaLink<sup>®</sup> C605 Colour Multifunction Printer

VersaLink<sup>®</sup> C605 Colour Multifunction Printers are built on Xerox<sup>®</sup> ConnectKey<sup>®</sup> Technology. For more information, go to <http://www.xerox.ca/en-ca/connectkey>.



SYSTEM SPECIFICATIONS	VERSALINK <sup>®</sup> 605
<b>One-sided Speed<sup>1</sup></b> 8.5 x 11 in. A4/210 x 297 mm 8.5 x 14 in./216 x 356 mm	Up to 55 ppm colour and black-and-white Up to 53 ppm colour and black-and-white Up to 45 ppm colour and black-and-white
<b>Two-sided Speed</b> 8.5 x 11 in. A4/210 x 297 mm 8.5 x 14 in./216 x 356 mm	Up to 52 ppm colour and black-and-white Up to 50 ppm colour and black-and-white Up to 26 ppm colour and black-and-white
<b>Monthly Duty Cycle<sup>2</sup></b>	Up to 120,000 pages/month
<b>Recommended Average Monthly Print Volume<sup>3</sup></b>	Up to 17,000 pages
<b>Hard Drive</b>	320 GB HDD
<b>Processor</b>	1.05GHz ARM Dual-Core
<b>Memory</b>	4 GB
<b>Connectivity</b>	Ethernet 10/100/1000 Base-T, High-speed USB 3.0, Wi-Fi 802.11n and Wi-Fi Direct with optional Wi-Fi Kit (concurrent wired and wireless connections supported), NFC Tap-to-Pair
<b>Controller Features</b>	Unified Address Book, Configuration Cloning, Scan Preview, Xerox Extensible Interface Platform <sup>®</sup> , Xerox <sup>®</sup> App Gallery App, Xerox <sup>®</sup> Standard Accounting Tool, Network Accounting Enabled, Role-Based Permissions, Convenience Authentication Enabled, Online Support
<b>User Interface Languages</b>	English, French, Italian, German, Spanish, Brazilian Portuguese, Russian, Dutch, Swedish, Danish, Finnish, Norwegian, Greek, Turkish, Polish, Czech, Hungarian, Romanian, Catalan, Ukrainian, Croatian

# Xerox® VersaLink® C605 Colour Multifunction Printer

DEVICE SPECIFICATIONS				
ELECTRICAL REQUIREMENTS				
<b>North America</b>	Voltage: 110-127V +/-10% Frequency: 50/60 Hz +/-3%, 12A			
<b>Europe and Other Geographies</b>	Voltage: 220-240V +/- 10% Frequency: 50/60 Hz +/-3%, 8A			
POWER CONSUMPTION				
<b>Continuous Printing<sup>4</sup></b>	820 watts or less			
<b>Ready (Standby) Mode<sup>4</sup></b>	90 watts or less			
<b>Energy Saver (Sleep) Mode<sup>4</sup></b>	0.9 watts or less			
OPERATING ENVIRONMENT				
<b>Required Temperature Range (Storage)</b>	32° to 95° F (0° to 35° C)			
<b>Required Temperature Range (Operating)</b>	50° to 90° F (10° to 32° C)			
<b>Required Relative Humidity</b>	15% to 85%			
<b>Sound Power Levels</b> Operating Standby	7.27 B(A) or less 4.84 B(A) or less			
<b>Sound Pressure Levels</b> Operating Standby	57.4 dB(A) or less 33.5 dB(A) or less			
<b>Boot Time (from Off to UI Ready)</b>	As fast as 65 seconds			
<b>Warm-up Time (from Sleep to UI Ready)</b>	As fast as 11 seconds			
DIMENSIONS AND WEIGHT (UNPACKAGED)	WIDTH	DEPTH	HEIGHT	WEIGHT
<b>Base Unit</b>	18.5 in./470 mm	19.8 in./503 mm	25.4 in./643.7 mm	79.6 lb./36.1 kg
<b>Base Unit with Mailbox</b>	19.2 in./487.5 mm	19.8 in./503 mm	33.2 in./843.7 mm	97.2 lb./44.1 kg
<b>Base Unit with Finisher</b>	19.2 in./487.5 mm	19.8 in./503 mm	33.2 in./843.7 mm	100.5 lb./45.6 kg
<b>Base Unit with High-Capacity Feeder and Finisher</b>	28.5 in./724.2 mm	30.4 in./772.1 mm	53.1 in./1302.7 mm	144 lb./65.3 kg
<b>Base Unit with High-Capacity Feeder and Mailbox</b>	28.5 in./724.2 mm	30.4 in./772.1 mm	53.1 in./1302.7 mm	140.5 lb./63.8 kg
<b>550-sheet Paper Tray</b>	16.5 in./420 mm	18.3 in./464.5 mm	4.8 in./123 mm	4.1 lb./6.6 kg
<b>High-Capacity Feeder (includes Caster Base)</b>	28.5 in./724.2 mm	30.4 in./772.1 mm	18.1 in./459 mm	43.4 lb./19.7 kg
<b>Cabinet (includes Caster Base)</b>	28.5 in./724.2 mm	30.4 in./772.1 mm	13.2 in./336 mm	37 lb./16.6 kg
<b>Caster Base</b>	28.5 in./724.2 mm	30.4 in./772.1 mm	3.5 in./90 mm	18.7 lb./8.5 kg
<b>Mailbox</b>	17.7 in./450.8 mm	18.8 in./477.6 mm	9.8 in./248.0 mm	11.7 lb./5.3 kg
<b>Finisher</b>	17.7 in./450.8 mm	16.2 in./411.0 mm	9.8 in./248.0 mm	15 lb./6.8 kg
DIMENSIONS AND WEIGHT (PACKAGED)	WIDTH	DEPTH	HEIGHT	WEIGHT
<b>Base Unit</b>	23.4 in./594 mm	25.8 in./655 mm	31.1 in./789 mm	97 lb./44 kg
<b>550-sheet Paper Tray</b>	21.1 in./535 mm	23 in./584 mm	9.8 in./248 mm	18.7 lb./8.5 kg

# Xerox® VersaLink® C605 Colour Multifunction Printer

<b>High-Capacity Feeder (includes Caster Base)</b>	22.4 in./568 mm	26.1 in./663 mm	28 in./711 mm	83.8 lb./38 kg
<b>Cabinet (includes Caster Base)</b>	23 in./584 mm	24.8 in./629 mm	23.5 in./597 mm	57.3 lb./28 kg
<b>Caster Base</b>	23 in./585 mm	24.4 in./619 mm	13 in./330 mm	39.7 lb./18 kg
<b>Mailbox</b>	22.6 in./573 mm	20.4 in./518 mm	15.2 in./386 mm	16.3 lb./7.8 kg
<b>Finisher</b>	22.6 in./573 mm	15.7 in./398 mm	15.2 in./386 mm	18.6 lb./8.8 kg
<b>CERTIFICATIONS</b>				
	To view the latest list of certifications, go to <a href="http://www.xerox.com/OfficeCertifications">www.xerox.com/OfficeCertifications</a> .			
<b>PRINT</b>				
<b>First-Print-Out Time</b>	As fast as 5.2 seconds colour/4.8 seconds black-and-white			
<b>Print Resolution</b>	Up to 1200 x 2400 dpi			
<b>Page Description Languages</b>	PCL® 5e, 6 PDF XPS TIFF JPEG HP-GL Adobe® PostScript® 3™			
<b>Maximum Print Area</b>	4 mm from edge of paper			
<b>Print Features</b>	<ul style="list-style-type: none"> <li>Application Defaults</li> <li>Banner Pages Enable/Disable</li> <li>Bi-directional Real-time Status</li> <li>Booklet Layout</li> <li>Draft Mode</li> <li>Fit to New Paper Size</li> <li>Job Identification (Print ID or Banner, Print ID in margins on first page only or all pages)</li> <li>Job Monitoring (Client or Local User Interface)</li> <li>LAN Fax (requires Fax Kit)</li> <li>N-up Page Layout (up to 16 pages per sheet)</li> <li>Paper Selection by Attribute</li> <li>Personal Print</li> <li>Print Around Enable/Disable</li> <li>Print from USB</li> <li>Sample Set</li> <li>Saved Job</li> <li>Scaling</li> <li>Secure Print</li> <li>Skip Blank Pages</li> <li>Special Pages (exception page programming covers, inserts, exceptions pages)</li> <li>Store and Recall Driver Settings</li> <li>Stored Jobs Deletion</li> <li>Two-sided Printing (as default)</li> <li>Watermark (predefined and custom)</li> <li>Earth Smart Driver Settings</li> </ul>			
<b>Print from USB</b>	<ul style="list-style-type: none"> <li>Allows walk-up printing from Type A USB port</li> <li>Supports direct printing from computer via Type B USB port</li> <li>Supported file formats: PDF, JPEG, TIFF, XPS, PDF/A</li> </ul>			

# Xerox® VersaLink® C605 Colour Multifunction Printer

<b>Operating Systems</b>	<p>Windows® 7, 8, 8.1, 10                  Windows Server 2008 SP2, Server 2008 R2 SP1, Server 2012, Server 2012 R2, Server 2016                  macOS® 10.11, 10.12, 10.13                  Citrix®                  Redhat® Enterprise Linux®                  Fedora Core                  IBM® AIX®                  HP-UX®                  Oracle® Solaris                  SUSE®                  SAP®</p> <p>Note: For information about supported versions for the above operating systems, please visit our Drivers &amp; Downloads page and specify your device at <a href="https://www.support.xerox.com/en-ca">https://www.support.xerox.com/en-ca</a>.</p>
<b>Fonts</b>	<p>PostScript fonts: 136                  PCL fonts: 83</p>
<b>Xerox® Global Print Driver®</b>	<p>A truly universal print driver that lets IT administrators install, upgrade and manage Xerox® and non-Xerox® devices from a single driver. It provides a consistent, easy-to-use interface for end-users, reducing the number of support calls, and simplifying print services management.</p>
<b>Xerox® Pull Print Driver</b>	<p>Makes it easy for IT managers to qualify, deploy and manage all print devices using a single driver in a Pull Print environment. Uses a single queue and single driver. The Xerox® Pull Print Driver extends convenience across a broad range of printing assets. IT administrators no longer need to manage and configure multiple drivers. Used in conjunction with Equitrac Office®, Ysoft® SafeQ®, Pharos® and others.</p>
<b>COPY</b>	
<b>Document Scanner</b>	<p>100-sheet Single-Pass Duplex Automatic Document Feeder (DADF)</p>
<b>Maximum Scan Area</b>	<p>Platen: Up to 8.5 x 14 in./216 x 356 mm                  DADF: Up to 8.5 x 14 in./216 x 356 mm</p>
<b>Simplex Copy Speed</b>	<p>Up to 55 cpm (copies per minute) 8.5 x 11 in.                  Up to 53 cpm A4/210 x 297 mm</p>
<b>Duplex Copy Speed</b>	<p>Up to 50 cpm (copies per minute) 8.5 x 11 in.                  Up to 47 cpm A4 (210 x 297 mm)</p>
<b>First-Copy-Out Time</b>	<p>As fast as 6.7 seconds colour/4.8 seconds black-and-white</p>
<b>Sides (input: output)</b>	<p>1:1, 1:2, 2:2 and 2:1</p>
<b>Quantity</b>	<p>1 to 999</p>
<b>Resolution (max.)</b>	<p>Up to 600 x 600 dpi</p>
<b>Reduction/Enlargement</b>	<p>Variable zoom from 25 % to 400 % in 1 % increments</p>
<b>Concurrency</b>	<p>Concurrent scanning and printing</p>

# Xerox® VersaLink® C605 Colour Multifunction Printer

<b>Copy Features</b>	<p>Annotation (Page Numbers, Comments, Date Stamp, Bates Stamping) including font format, colour and style options*</p> <p>Auto-colour Sensing</p> <p>Automatic Background Suppression</p> <p>Book Copying with Center Erase</p> <p>Booklet Copying*</p> <p>Collation</p> <p>Colour Balance</p> <p>Colour Effects</p> <p>Darkness Control</p> <p>Edge Erase</p> <p>Front Cover</p> <p>ID Card Copy</p> <p>Image Enhancement</p> <p>Lighten/Darken</p> <p>N-up</p> <p>Reduce/Enlarge 25% to 400%</p> <p>Image Shift</p> <p>Original Orientation</p> <p>Original Size</p> <p>Original Type</p> <p>Page Layout</p> <p>Sample Copy</p> <p>Saturation</p> <p>Sharpness</p> <p>*Requires HDD/Productivity Kit</p>
<b>SCAN</b>	
<b>Capability</b>	Black-and-white and colour scanning
<b>Concurrency</b>	Scan while the system is printing copy or network print jobs, or while it is transferring scan to network or fax jobs
<b>Simplex Input Speed</b>	Black-and-white: Scan up to 49 ipm 8.5 x 11 in./46 ipm A4 Colour: Scan up to 47 ipm 8.5 x 11 in./46 ipm A4
<b>Duplex Input Speed</b>	Black-and-white: Scan up to 75 ipm 8.5 x 11 in./71 ipm A4 Colour: Scan up to 55 ipm 8.5 x 11 in./52 ipm A4
<b>Resolution</b>	Optical – 600 x 600 dpi
<b>Bit Depth</b>	24-bit colour/8-bit grayscale
<b>Maximum Scan Area</b>	Platen: Up to 8.5 x 14 in./216 x 356 mm Document Feeder: Up to 8.5 x 14 in./216 x 356 mm
<b>Network Filing Protocols</b>	FTP SMTP SMB sFTP
<b>File Formats</b>	JPG TIFF (single and multi-page) XPS (single and multi-page) PDF (single and multi-page) Searchable PDF via Optical Character Recognition (OCR) Password-protected PDF Linearized PDF (set via embedded web server) and PDF/A
<b>Scan Driver Compatibility</b>	WIA TWAIN
<b>Supported Scan Destinations</b>	Scan to Home Scan to USB Scan to Email Scan to Network (Browse FTP or Browse SMB)

<b>NETWORK SCANNING – SOFTWARE SOLUTIONS</b>	
<b>Xerox® ConnectKey® Apps (Found at the Xerox App Gallery)</b>	Increase user productivity by simplifying and shortening everyday tasks. Unlike traditional software, ConnectKey® Apps do not require a dedicated server, PC or IT resource. Instead, simply download these lightweight, serverless ConnectKey® Apps to the ConnectKey® Technology-enabled device.
<b>FAX<sup>5</sup></b>	
<b>Fax Speed</b>	33.6 Kbps
<b>Memory</b>	4 MB
<b>Resolution</b>	Standard 200x100 dpi, Fine 200x200 dpi, Super Fine 300x300, 400x400, 600x600 dpi
<b>Compression</b>	MH, MR, MMR, JBIG
<b>Fax Features</b>	Walk-up Fax, LAN Fax, Direct Fax, Server Fax Enablement, Fax Forward to Email Fax dialling via Unified Address Book (up to 2,000 contacts)
<b>MOBILE SOLUTIONS AND MOBILE DEVICE APPS</b>	
<b>Apple® AirPrint®</b>	Print email, photos and important office documents directly from an Apple iPhone® or iPad® with no drivers to install and no cables to connect. With AirPrint, an iPhone or iPad automatically locates and connects to the AirPrint-enabled device over the office Wi-Fi network.
<b>Mopria® Certified</b>	ConnectKey® Technology-enabled print devices are Mopria® certified. Mopria® certification ensures you can print wirelessly from your Mopria® supported (Android) smartphone, tablet and other mobile devices instantly and easily.
<b>Xerox® @printbyXerox App</b>	@printbyXerox App is a free service that allows secure printing from any email-enabled device (computer, phone, tablet, iOS, Android™, Google® Chromebook™ and more) to a Xerox® printer or MFP using a single email address with no IT intervention. No training is needed. End-users simply send attachments to the email address and release them at the MFP panel.
<b>Xerox® Print Services plug-in for Android™ (Free at Google Play™ Store)</b>	The Xerox® Print Services plug-in for Android KitKat (4.4 or greater) devices streamlines mobile printing without third-party apps or additional print drivers. You can easily print photos, web pages and documents when your mobile device is connected to printers or multifunction printers using a wireless network. A robust print option set includes two-sided printing, stapling and secure code release. A free download is available from the Google Play™ store.
<b>Xerox® Mobile Link App (Free at Google Play™ Store and Apple® App Store)</b>	The Xerox® Mobile Link App allows you to scan, email and fax from your phone or tablet by connecting with our multifunction printers and send data to and print data from cloud storage. It is easy to create Mobile Link One-Touch Workflows between a mobile device and a Multifunction Printer. Using a manual address or QR code identification for pairing, automatic device discovery makes it easy to find and pair a mobile device with a nearby Xerox® Multifunction Printer.
<b>Xerox® Workplace Suite and Xerox® Workplace Cloud</b>	Xerox® Workplace Suite is a modular set of workflows designed to save customers time and money by providing effective control over their print fleet while enabling worker productivity and mobility through a set of robust workflows. Xerox enables ultimate customer flexibility by offering these capabilities in both an on-premises server version (Workplace Suite) and with a cloud based-version (Workplace Cloud) of this solution.

SECURITY	
<b>Security Features</b>	Access Controls AES 256-bit Encryption Audit Log Certificate Path Validation Certificate Revocation List (CRL)/Status Protocol (OCSP) Detection of External Program Falsification (XCP Plug-in) Cisco® Identity Services Engine (ISE) Integration Domain Filtering FIPS 140-2 Firmware Verification Immediate Disk Overwrite* IP Address Filtering IPsec Network Authentication Port Filtering Pre-installed Self-Signed Certificates Role-Based Permissions Secure Email Secure Fax Secure Print Secure Scanning via SFTP Security Certificate Management Smart Card Enablement (CAC/PIV/.NET) SNMPv3 TLS/SSL Trusted Platform Module (TPM)  *Requires HDD/Productivity Kit
ACCOUNTING	
XEROX® STANDARD ACCOUNTING/NETWORK ACCOUNTING (STANDARD)	
<b>Tracking</b>	Copy, Print, Fax, Scan and Email usage
<b>Accounting</b>	Xerox® Standard Accounting Tool Up to 1,000 User Accounts without HDD Up to 9,999 User Accounts with HDD Up to 500 General Accounts  Network Accounting (Job Based Accounting) Up to 1,000 User IDs; Up to 1,000 Account IDs without HDD Up to 60,000 User IDs; Up to 60,000 Account IDs with HDD Up to 14,000 Accounting Records (transactions)
<b>Features</b>	Administrator can manage the feature via the Embedded Web Server
ACCOUNTING OPTIONS – NETWORK ACCOUNTING (ALLOWS CENTRAL SERVER TO MANAGE ALL ACCOUNTING)	
	<ul style="list-style-type: none"> <li>Enhanced network accounting with up to the minute data on how the system is being used</li> <li>Comprehensive management and enterprise-scale tracking and reporting of device usage</li> <li>Numerous solutions are available through Xerox Alliance Partners. For details visit <a href="https://www.xerox.ca/">https://www.xerox.ca/</a></li> <li>Security enhancements include simultaneous support for HTTP/HTTPS protocols</li> <li>Device requests account authentication from third-party server enabling larger databases of users and accounts</li> <li>Accept Authentication Login at control panel and pass to third-party Networking Account</li> </ul>

# Xerox® VersaLink® C605 Colour Multifunction Printer

<b>PAPER HANDLING</b>	
<b>DOCUMENT FEEDER</b>	
<b>Capacity<sup>6</sup></b>	Single-Pass Duplex Automatic Document Feeder (DADF): 100 sheets
<b>Sizes</b>	Custom sizes: 5.5 x 5.5 in. to 8.5 x 14 in./140 x 140 mm to 216 x 356 mm
<b>Weights</b> One-sided: Two-sided:	16 to 32 lb. bond/60 to 128 gsm 16 to 32 lb. bond/60 to 128 gsm
<b>BYPASS TRAY</b>	
<b>Capacity<sup>6</sup></b>	150 sheets
<b>Sizes</b>	Custom sizes: 3 x 5 in. to 8.5 x 14 in./76 x 127 mm to 216 x 356 mm
<b>Weights</b> One-sided: Two-sided:	16 lb. bond to 80 lb. cover/60 to 220 gsm 16 lb. bond to 65 lb. cover/60 to 176 gsm
<b>Media Types</b>	Bond Plain Paper Cardstock Custom Envelopes Hole Punched Labels Letterhead Lightweight Cardstock Pre-Printed Recycled
<b>TRAY 1 :</b>	
<b>Capacity<sup>6</sup></b>	550 sheets
<b>Sizes</b>	Custom sizes: 3 x 7.5 in. to 8.5 x 14 in./76 x 190 mm to 216 x 356 mm
<b>Weights</b> One-sided: Two-sided:	16 lb. bond to 80 lb. cover/60 to 220 gsm 16 lb. bond to 65 lb. cover/60 to 176 gsm
<b>Media Types</b>	Bond Plain Paper Cardstock Custom Hole Punched Labels Letterhead Lightweight Cardstock Heavyweight Cardstock Pre-Printed Recycled Envelope



# Xerox® VersaLink® C605 Colour Multifunction Printer

<b>UP TO FOUR ADDITIONAL TRAYS (OPTIONAL)</b>	
<b>Capacity<sup>6</sup></b>	550 sheets
<b>Sizes</b>	Custom sizes: 3 x 7.5 in. to 8.5 x 14 in./76 x 190 mm to 216 x 356 mm
<b>Weights</b> One-sided: Two-sided:	16 lb. bond to 80 lb. cover/60 to 220 gsm 16 lb. bond to 65 lb. cover/60 to 176 gsm
<b>Media Types</b>	Bond Plain Paper Cardstock Custom Hole Punched Labels Letterhead Lightweight Cardstock Heavyweight Cardstock Pre-Printed Recycled
<b>HIGH-CAPACITY FEEDER (ONLY ONE ADDITIONAL 550-SHEET TRAY CAN BE ADDED TO HIGH-CAPACITY FEEDER)</b>	
<b>Capacity<sup>6</sup></b>	2,000 sheets
<b>Sizes</b>	Letter/A4
<b>Weights</b> One-sided: Two-sided:	16 lb. bond to 65 lb. cover/60 to 176 gsm 16 lb. bond to 65 lb. cover/60 to 176 gsm
<b>Media Types</b>	Bond Plain Paper Hole Punched Letterhead Lightweight Cardstock Pre-Printed Recycled
<b>TOTAL CAPACITY</b>	
<b>Standard Device Capacity<sup>6</sup></b>	700 sheets
<b>Maximum Device Capacity<sup>6</sup></b>	3,250 sheets
<b>PAPER OUTPUT/FINISHING</b>	
<b>Capacity<sup>6</sup></b>	Up to 400 sheets
<b>Automatic Two-sided Printing</b>	Standard
<b>FINISHER</b>	
<b>Capacity<sup>6</sup></b>	500-sheet tray, 50-sheet stapling
<b>MAILBOX</b>	
<b>Capacity<sup>6</sup></b>	Four 100-sheet bins

# Xerox® VersaLink® C605 Colour Multifunction Printer

DEVICE MANAGEMENT	
<b>Network Protocols</b>	TCP/IP: HTTP/HTTPS, Internet Printing Protocol, LPR/LPD, Raw Socket Printing/Port 9100, IPv4/IPv6, WSD LDAP Bonjour®/AirPrint™ FTP Most protocols not in use can be disabled
<b>Administrative Protocols</b>	DHCP, SNMP, WINS, HTTP, HTTPS, TLS, SNTP, MDNS
REMOTE CONTROL PANEL	
	<ul style="list-style-type: none"> <li>• Enables faster, more convenient technical support and user training</li> <li>• IT administrators and other authorized users can control the device remotely from a web page on any device</li> <li>• Remote user experience is identical to performing tasks directly at the device</li> </ul>
XEROX® CENTREWARE® WEB SOFTWARE	
	<ul style="list-style-type: none"> <li>• A web-based server application for network administrators that permits web browser-based device management from any workstation, whether running Windows or UNIX or any other operating system</li> <li>• Works with any SNMP-managed printer from any manufacturer</li> <li>• Provides help with device discovery and installations, health checks and troubleshooting, and device upgrades, as well as basic accounting and asset management</li> </ul>
XEROX® EMBEDDED WEB SERVER – INTEGRATED DEVICE WEB PAGE	
<b>Device Status</b>	<ul style="list-style-type: none"> <li>• Tray Status/Contents</li> <li>• Consumables Status</li> <li>• Billing/Usage</li> <li>• Quick Links</li> <li>• Online Support</li> </ul>
<b>Print Queue Viewing</b>	Job print queue management — view and delete
<b>Job submission</b>	Print-ready files (PS, PCL, PDF, XPS, JPEG)
<b>Device Administration</b>	Allows simple, remote installation setting of configuration options and management of the device
<b>Browsers</b>	Microsoft® Internet Explorer® Microsoft Edge™ Mozilla™ Firefox® Apple® Safari® Google Chrome™
REMOTE SERVICES	
<b>Automated Meter Readings (AMR)</b>	Automates the process of collecting and submitting meter reads for tracking and billing of Xerox® device usage. Eliminates the need for time-consuming end-user involvement and ensures that meter reads are submitted to Xerox on time.
<b>Automatic Supplies Replenishment (ASR)</b>	Automatically orders supplies for Xerox® output devices based on actual usage, eliminating the need to manually manage supplies inventory.
WHAT'S IN THE BOX	
	VersaLink® C605 Colour Multifunction Printer Starter Capacity Print Cartridge: One of each (Cyan, Magenta, Yellow): 6,000 print capacity <sup>7</sup> , Black: 10,000 print capacity <sup>7</sup> Software and Documentation CD (Safety, Regulatory, Recycling and Disposal Guides, Print Drivers, and Warranty Statement) Installation Guide Quick Use Guides Power Cord Fax Cord

# Xerox® VersaLink® C605 Colour Multifunction Printer

SUPPLIES AND ACCESSORIES	QUANTITY	PART NUMBER
<b>SUPPLIES</b>		
<b>Standard Capacity Toner Cartridges</b>	Black: 6,000 standard pages <sup>7</sup> Cyan: 6,000 standard pages <sup>7</sup> Magenta: 6,000 standard pages <sup>7</sup> Yellow: 6,000 standard pages <sup>7</sup>	106R03899 106R03896 106R03897 106R03898
<b>High Capacity Toner Cartridges</b>	Black: 12,200 standard pages <sup>7</sup> Cyan: 10,100 standard pages <sup>7</sup> Magenta: 10,100 standard pages <sup>7</sup> Yellow: 10,100 standard pages <sup>7</sup>	106R03903 106R03900 106R03901 106R03902
<b>Extra-High Capacity Toner Cartridges</b>	Black: 16,900 standard pages <sup>7</sup> Cyan: 16,800 standard pages <sup>7</sup> Magenta: 16,800 standard pages <sup>7</sup> Yellow: 16,800 standard pages <sup>7</sup>	106R03931 106R03928 106R03929 106R03930
<b>ROUTINE MAINTENANCE ITEMS</b>		
<b>Drum Cartridges</b>	Cyan: 40,000 pages <sup>8</sup> Magenta: 40,000 pages <sup>8</sup> Yellow: 40,000 pages <sup>8</sup> Black: 40,000 pages <sup>8</sup>	108R01485 108R01486 108R01487 108R01488
<b>Waste Cartridge</b>	30,000 pages <sup>8</sup>	108R01416
<b>ACCESSORIES</b>		
<b>550-sheet Feeder</b>		097S04949
<b>2,000-sheet High-Capacity Feeder (includes Caster Base)</b>		097S04948
<b>Cabinet (includes stabilizers)</b>		097S04994
<b>Caster Base</b>		097S04954
<b>Finisher (500 sheets, 50-sheet stapler)</b>		097S04952
<b>4-Bin Mailbox (100 sheets per bin)</b>		097S04953
<b>Productivity Kit with 320 GB HDD</b>		497K18360
<b>Wireless Network Adapter (Wi-Fi Kit)</b>		497K16750
<b>Internal Card Reader/RFID Kit</b>		497K18120

<sup>1</sup> Declared print speed in accordance with ISO/IEC 24734.

<sup>2</sup> Maximum volume capacity expected in any one month. Not expected to be sustained on a regular basis.

<sup>3</sup> Recommended average throughput is not a minimum but is intended to cover a range of volumes for different environments.

<sup>4</sup> Power states defined per ENERGY STAR® Program requirements for Imaging Equipment.

<sup>5</sup> Requires analog phone line.

<sup>6</sup> Paper capacities are based on 20 lb./75 gsm stock; capacities will vary with different weight stocks.

<sup>7</sup> Average standard pages. Declared Yield in accordance with ISO/IEC19798. Yield will vary based on image, area coverage and print mode.

<sup>8</sup> Approximate pages. Declared yield will vary depending on job run length, media size/orientation and machine speed. For more information visit: <https://www.office.xerox.com/latest/SUPGL-01.pdf>

Return spent imaging supplies through the Xerox Green World Alliance collection/reuse/recycling program.

For more information, visit <https://www.xerox.ca/about-xerox/recycling/enca.html>.

For more information, visit us at <http://www.xerox.ca/office>.

Configurations vary by geography.