


Xerox® VersaLink® Color Multifunction Printer

C7020/C7025/C7030

VersaLink C7000 Series Color Multifunction Printers are built on Xerox® ConnectKey® Technology. For more information, go to www.connectkey.com.



System Specifications	VersaLink C7020	VersaLink C7025	VersaLink C7030
One-Sided Speed 8.5 x 11 in. / A4 / 210 x 297 mm 8.5 x 14 in. / 216 x 356 mm 11 x 17 in. / A3 / 297 x 420 mm	Up to 20 ppm (pages per minute) long edge feed (LEF) Up to 16 ppm 8.5 x 14 in. / 216 x 356 mm Up to 11 ppm 11 x 17 in. / A3 / 297 x 420 mm	Up to 25 ppm (LEF) Up to 19 ppm 8.5 x 14 in. / 216 x 356 mm Up to 14 ppm 11 x 17 in. / A3 / 297 x 420 mm	Up to 30 ppm (LEF) Up to 23 ppm 8.5 x 14 in. / 216 x 356 mm Up to 17 ppm 11 x 17 in. / A3 / 297 x 420 mm
Monthly Duty Cycle¹	Up to 87,000 pages / month ¹	Up to 107,000 pages / month ¹	Up to 129,000 pages / month ¹
Recommended Average Monthly Print Volume²	Up to 5,500 pages	Up to 6,250 pages	Up to 7,000 pages
Hard Drive	320 GB HDD (Optional on Desktop\Base Unit)		
Processor	1.05 GHz Dual-Core		
Memory	4 GB		
Connectivity	Ethernet 10/100/1000 Base-T, High-speed USB 3.0, Wi-Fi 802.11n/g/b/a and Wi-Fi Direct with optional Wi-Fi Kit (concurrent wired and wireless connections supported), NFC Tap-to-Pair		
Controller Features	Unified Address Book, Configuration Cloning, Scan Preview, Fax Preview, Xerox Extensible Interface Platform®, Xerox App Gallery, Xerox® Standard Accounting, Role Based Permissions, Convenience Authentication Enabled, Online Support		

Xerox® VersaLink® C7020/C7025/C7030 Color Multifunction Printer

Device Specifications				
Electrical Requirements				
North America	Voltage : 110-127V -10% / +6 % Frequency: 50/60 Hz +/-3% , 12A			
Europe	Voltage : 220-240V +/- 10 % Frequency: 50 Hz +/-3% , 8A			
Power Consumption				
Printing ⁵	For 110V: 20 ppm = 0.9 kWh; 25 ppm = 1.1 kWh; 30 ppm = 1.5 kWh For 220V: 20 ppm = 0.9 kWh; 25 ppm = 1.1 kWh; 30 ppm = 1.5 kWh			
Standby Mode ⁵	110V: 80 Watts or less 220V: 80 Watts or less	110V: 80 Watts or less 220V: 80 Watts or less	110V: 94 Watts or less 220V: 94 Watts or less	
Sleep Mode ⁵	110V: 1.0 watts or less 220V: 1.4 watts or less			
Operating Environment				
Required Temperature Range (Storage)	32° to 95° F (0° to 35° C)			
Required Temperature Range (Operating)	50 to 90° F (10 to 32° C)			
Required Relative Humidity	10% to 85%			
Sound Power Levels	Printing: 6.70 B(A) or less <ul style="list-style-type: none"> 20 ppm = 6.45 B(A); 25 ppm = 6.50 B(A); 30 ppm = 6.70 B(A) Standby: 4.10 B(A) or less <ul style="list-style-type: none"> 20 ppm = 4.10 B(A); 25 ppm = 4.10 B(A); 30 ppm = 4.10 B(A) Full System (including finisher and HCF) Printing: 20 ppm = 7.07 B(A); 25 ppm = 7.22 B(A); 30 ppm = 7.37 B(A) Standby: 20 ppm = 4.10 B(A); 25 ppm = 4.10 B(A); 30 ppm = 4.10 B(A)			
Sound Pressure Levels	Printing: 52.0 dB(A) <ul style="list-style-type: none"> 20 ppm = 49.5 dB(A); 25 ppm = 50.0 dB(A); 30 ppm = 52.0 dB(A) Standby: 26.0 dB(A) <ul style="list-style-type: none"> 20 ppm = 26.0 dB(A); 25 ppm = 26.0 dB(A); 30 ppm = 26.0 dB(A) Full System (including finisher and HCF) Printing: 20 ppm = 55.5 dB(A); 25 ppm = 57.0 dB(A); 30 ppm = 58.5 dB(A) Standby: 20 ppm = 26.0 dB(A); 25 ppm = 26.0 dB(A); 30 ppm = 26.0 dB(A)			
Boot Time (from Off to UI Ready)	As fast as 98 seconds			
Warm-up Time (from Sleep to UI Ready)	As fast as 12 seconds			
Dimensions and Weight (Unpackaged)	Width	Depth	Height	Weight
Base Unit	23.23 in. / 590 mm	26.41 in. / 670.8 mm	30.23 in. / 767.9 mm	152.12 lbs. / 69.0 kg
Base Unit with Single Tray with Stand Module	24.24 in. / 615.7 mm	26.41 in. / 670.8 mm	44.04 in. / 1118.6 mm	203.49 lbs. / 92.3 kg
Base Unit with High Capacity Tandem Tray Module	24.24 in. / 615.7 mm	26.41 in. / 670.8 mm	44.04 in. / 1118.6 mm	234.79 lbs. / 106.5 kg
Base Unit with Three Tray Module	24.24 in. / 615.7 mm	26.41 in. / 670.8 mm	44.04 in. / 1118.6 mm	212.75 lbs. / 96.5 kg
Base Unit with Three Tray Module and Office Finisher LX (with Booklet Maker)	47.0 in. / 1194.0 mm	26.8 in. / 681.8 mm	44.04 in. / 1118.6 mm	296.3 lbs. / 134.4 kg

Xerox® VersaLink® C7020/C7025/C7030 Color Multifunction Printer

Certifications			
To view the latest list of certifications, go to www.xerox.com/OfficeCertifications .			
Print			
First-print-out Time	As fast as 9.4 seconds Color	As fast as 9.4 seconds Color	As fast as 7.3 seconds Color
	As fast as 7.2 seconds Black	As fast as 7.1 seconds Black	As fast as 5.6 seconds Black
Print Resolution	Up to 1200 x 2400 dpi		
Page Description Languages	PCL® 5e, 6 PDF XPS TIFF JPEG HP-GL Adobe® PostScript® 3™ (Optional)		
Maximum Print Area	4 mm from lead edge of paper, 2 mm from Side and Trail edges of paper		
Print Features	Application Defaults Bi-directional Real-time Status Booklet Creation Draft Mode Job Identification Job Monitoring Personal Print Print from USB Sample Set Saved Job Scaling Secure Print Skip Blank Pages Store and Recall Driver Settings Two-sided Printing (as default) Xerox® Earth Smart Driver Settings		
Print from USB	Allows walk-up printing from Type A USB port Supports direct printing from computer via Type B USB port Supported file formats: PDF, JPEG, TIFF, XPS		
Operating Systems	Windows®, 7, 8, 10, Server 2000, Server 2003, Server 2008, Server 2008 R2 Server 2012 Mac OS® version 10.10, 10.11, & 10.12 Citrix Redhat® Enterprise Linux® IBM® AIX® 7.2 HP-UX® 11iv3 Oracle® Solaris 11.3 Fedora Core 24 SUSE® 13.2		
Fonts	PostScript fonts: 136 PCL fonts: 83		

Xerox® VersaLink® C7020/C7025/C7030 Color Multifunction Printer

Copy			
Document Scanner	110-sheet Duplex Automatic Document Feeder (DADF)		
Document Scanner Size	Platen: Up to 13.1 x 17.2 in. / 332.0 x 437 mm DADF: Up to 11.7 x 17 in. / 297 x 431.8 mm		
Simplex Copy Speed	Up to 20 cpm (copies per minute) 8.5 x 11 in. Up to 20 cpm A4 (210 x 297 mm)	Up to 25 cpm (copies per minute) 8.5 x 11 in. Up to 25 cpm A4 (210 x 297 mm)	Up to 30 cpm (copies per minute) 8.5 x 11 in. Up to 30 cpm A4 (210 x 297 mm)
Duplex Copy Speed	Up to 17 cpm (copies per minute) 8.5 x 11 in. Up to 17 cpm A4 (210 x 297 mm)	Up to 18 cpm (copies per minute) 8.5 x 11 in. Up to 18 cpm A4 (210 x 297 mm)	Up to 18 cpm (copies per minute) 8.5 x 11 in. Up to 18 cpm A4 (210 x 297 mm)
First-copy-out Time	As fast as 9.0 seconds Color	As fast as 9.0 seconds Color	As fast as 7.2 seconds Color
	As fast as 6.9 seconds Black	As fast as 6.9 seconds Black	As fast as 5.8 seconds Black
Sides (input:output)	1:1, 1:2, 2:2 and 2:1		
Quantity	1 to 999		
Resolution (max.)	Up to 600 x 600 dpi		
Reduction / Enlargement	Variable zoom from 25 % to 400 % in 1 % increments		
Concurrency	Concurrent scanning and printing		
Copy Features	Automatic Background Suppression Book Copying with Center Erase Booklet Creation (requires HDD) Annotations (Page Numbers, Comments, Date Stamp, Bates Stamp) (requires HDD) Collation Darkness Control Edge Erase ID Card Copy N-up Reduce / Enlarge 25 % to 400 % Image Shift Original Type Sample Copy Sharpness		
Scan			
Capability	Black and white and color scanning		
Concurrency	Scan while the system is printing copy or network print jobs, or while it is transferring scan to network or fax jobs		
Simplex Input Speed	Black and white: Scan up to 55 ipm – 8.5 x 11 in. / A4 (210 x 297 mm) Color: Scan up to 55 ipm – 8.5 x 11 in. / 55 ipm A4 (210 x 297 mm)		
Duplex Input Speed	Black and white: Scan up to 26 ipm – 8.5 x 11 in. / A4 (210 x 297 mm) Color: Scan up to 26 ipm – 8.5 x 11 in. / 26 ipm A4 (210 x 297 mm)		
Resolution	Optical – 600 x 600 dpi		
Bit Depth	24-bit color / 8-bit grayscale		
Maximum Scan Area	Platen: Up to 13.1 x 17.2 in. / 332 x 437 mm Document Feeder: 11.7 x 17 in. / 297 x 431.8 mm		
Network Filing Protocols	FTP SMTP SMB		

Xerox® VersaLink® C7020/C7025/C7030 Color Multifunction Printer

File Formats	JPG TIFF (single and multi-page) XPS (single and multi-page) PDF (single and multi-page) Searchable PDF Password-protected PDF Linearized PDF (set via embedded web server) and PDF/A
Scan Driver Compatibility (Network Only)	WIA TWAIN
Supported Scan Destinations	Scan to Home Scan to USB Scan to Email Scan to Network (Browse FTP or Browse SMB)
Network Scanning – Software Solutions	
Xerox® ConnectKey® Apps (Found at the Xerox® App Gallery)	Increase user productivity by simplifying and shortening everyday tasks. Unlike traditional software, ConnectKey Apps do not require a dedicated server, PC or IT resource. Instead, simply download these lightweight, serverless ConnectKey Apps to the ConnectKey-enabled multifunction printer.
PSTN One-line or Three-line Fax (Optional)	
Fax³	
Fax Speed	33.6 Kbps
Resolution	Up to 600 x 600 dpi resolution
Compression	MH, MR, MMR, JBIG
Fax Features	Walk-up Fax, includes LAN Fax, Direct Fax, Fax Forward to Email Fax dialing via Unified Address Book (up to 2,000 contacts)
Fax over IP (Optional)	
Compliance	T.38 compliant IP / SIP
Resolution	Up to 600 x 600 dpi resolution
Compression	MH, MR, MMR, JBIG
Fax Features	Walk-up Fax, includes LAN Fax, Direct Fax, Fax Forward to Email Fax dialing via Unified Address Book (up to 2,000 contacts)
Mobile Solutions and Mobile Device Apps	
Xerox® Mobile Express Driver®	Makes it easy for mobile users to find, use and manage Xerox® and non-Xerox® devices in every new location. Plug into a new network, and Mobile Express Driver automatically discovers available printers and provides status and capability information. Save a list of “favorite” printers for each location, store application print settings for use on any printer in any network, and greatly reduce mobile support calls to IT.
Xerox® Global Print Driver®	A truly universal print driver that lets IT administrators install, upgrade and manage Xerox® and non-Xerox® devices from a single driver. It provides a consistent, easy-to-use interface for end-users, reducing the number of support calls, and simplifying print services management.
Apple® AirPrint®	Print email, photos and important office documents directly from an Apple iPhone® or iPad® with no drivers to install and no cables to connect. With AirPrint, an iPhone or iPad automatically locates and connects to the AirPrint-enabled device over the office Wi-Fi network.
Google Cloud Print™	Google Cloud Print connects print devices to the web, enabling users to print the applications they use every day from smartphones, tablets, Chromebook™ notebook computers and any other web-connected device.
Xerox® Print Service Plug-in for Android™ (Free at Google Play™ Store)	The Xerox® Print Service Plug-in for Android KitKat (4.4 or greater) devices streamlines mobile printing without third-party apps or additional print drivers. You can easily print photos, Web pages and documents when your mobile device is connected to multifunction printers using a wireless network. A robust print option set includes two-sided printing, stapling and secure code release. A free download is available from the Google Play™ store.

Xerox® VersaLink® C7020/C7025/C7030 Color Multifunction Printer

Xerox® Mobile Link App (Free at Google Play™ Store and Apple® App Store)	The Xerox® Mobile Link App allows you to scan, email and fax from your phone or tablet by connecting with our multifunction printers and send data to and print data from cloud storage. It is easy to create Mobile Link One-Touch Workflows between a mobile device and a multifunction printer. Using a manual address or QR code identification for pairing, automatic device discovery makes it easy to find and pair a mobile device with a nearby Xerox® multifunction printer.
Xerox® Print Management and Mobility Suite, Xerox® Print Management and Mobility Service	Xerox® Print Management and Mobility Suite is a modular set of workflows designed to save customers time and money by providing effective control over their print fleet, while enabling worker productivity and mobility through a set of robust workflows. Xerox enables ultimate customer flexibility by offering these capabilities in both an on-premises server version and with a cloud based-version of this solution.
Security	
Standard Security Features	Firmware Verification Security Certificate Management Automatic Self-Signed Certificate Creation Certificate Revocation List (CRL)/Online Certificate Status Protocol (OCSP) Certificate Path Validation Immediate Disk Overwrite (requires HDD) AES 256-bit Encryption FIPS 140-2 TLS/SSL SNMPv3 Smart Card Enablement (CAC/PIV/.NET) Detection of external program falsification (XCP Plug-in) Network Authentication Access Controls Role Based Permissions Domain Filtering IP Address Filtering Port Filtering Audit Log Secure Email Secure Fax Secure Print Secure Scan
Accounting	
Xerox® Standard Accounting / Network Accounting (Standard)	
Tracking	Copy, Print, Fax, Scan and Email usage
Accounting	Xerox® Standard Accounting Tool Up to 9,999 User Accounts with HDD installed Up to 1,000 User Accounts without HDD installed Network Accounting (Job Based Accounting) Up to 60,000 User IDs; Up to 60,000 Account IDs with HDD installed Up to 1,000 User IDs; Up to 1,000 Account IDs without HDD installed Up to 14,000 accounting records (transactions)
Features	Administrator can manage the feature via the Embedded Web Server or local user interface on device
Accounting Options – Network Accounting (Allows central server to manage all accounting)	
	<ul style="list-style-type: none"> • Enhanced network accounting with up to the minute data on how the system is being used • Comprehensive management and enterprise scale tracking and reporting of device usage of copy, print, scan and fax • Numerous solutions are available through Xerox Alliance Partners. For details visit www.xerox.com • Security enhancements includes support for HTTPS protocol • Device requests account authentication from third party server enabling larger databases of users and accounts Accept Authentication Login at control panel and pass to third party Networking Account

Xerox® VersaLink® C7020/C7025/C7030 Color Multifunction Printer

Paper Handling	
Document Feeder	
Capacity⁴	Duplex Automatic Document Feeder (DADF): 110 sheets
Sizes	Custom sizes: Duplex: 4.92 x 4.33 in. to 11.69 x 17 in. / 125 x 110 mm to 297 x 431.8 mm; Simplex: 4.92 x 3.35 in. to 11.69 x 17 in. / 125 x 85 mm to 297 x 431.8 mm
Weights	Simplex: 11 lb. bond to 34 lb. bond / 38 –128 gsm Duplex: 13 lb. bond to 34 lb. bond / 50 –128 gsm
Bypass Tray	
Capacity⁴	100 sheets
Sizes	Custom sizes: 3.5 x 3.87 in. to 11.69 x 17 in. / 88.9 x 98.4 mm to 297 x 431.8 mm
Weights	16 lb. bond to 80 lb. cover / 60 to 216 gsm
Types	Bond Plain Paper Cardstock Custom Envelopes Hole Punched Labels Heavyweight Labels Letterhead Lightweight Cardstock Lightweight Glossy Cardstock Lightweight Glossy Cardstock Reload Pre-Printed Recycled
Tray 1	
Capacity⁴	520 sheets
Sizes	Custom sizes: 5.5 x 7.17 in. to 11.69 x 17 in. / 139.7 x 182.0 mm to 297.0 x 431.8 mm
Weights	16 lb. bond to 95 lb. cover / 60 to 256 gsm
Types	Bond Plain Paper Cardstock Custom Hole Punched Labels Heavyweight Labels Extra Heavyweight Labels Letterhead Lightweight Cardstock Lightweight Glossy Cardstock Lightweight Glossy Cardstock Reload Heavyweight Cardstock Pre-Printed Recycled
Single Tray Module (Optional – Base Model only)	
Capacity⁴	520 sheets
Sizes	Custom sizes: 5.5 x 7.17 in. to 11.69 x 17 in. / 139.7 x 182.0 mm to 297.0 x 431.8 mm
Weights	16 lb. bond to 95 lb. cover / 60 to 256 gsm

Xerox® VersaLink® C7020/C7025/C7030 Color Multifunction Printer

Types	<ul style="list-style-type: none"> Bond Plain Paper Cardstock Custom Hole Punched Labels Heavyweight Labels Extra Heavyweight Labels Letterhead Lightweight Cardstock Lightweight Glossy Cardstock Lightweight Glossy Cardstock Reload Heavyweight Cardstock Pre-Printed Recycled
Single Tray Module with Stand (Optional)	
Capacity⁴	520 sheets
Sizes	Custom sizes: 5.5 x 7.17 in. to 11.69 x 17 in. / 139.7 x 182.0 mm to 297.0 x 431.8 mm
Weights	16 lb. bond to 95 lb. cover / 60 to 256 gsm
Types	<ul style="list-style-type: none"> Bond Plain Paper Cardstock Custom Hole Punched Labels Heavyweight Labels Extra Heavyweight Labels Letterhead Lightweight Cardstock Lightweight Glossy Cardstock Lightweight Glossy Cardstock Reload Heavyweight Cardstock Pre-Printed Recycled
Three Tray Module (Optional)	
Capacity⁴	<ul style="list-style-type: none"> Tray 2: 520 sheets Tray 3: 520 sheets Tray 4: 520 sheets
Sizes	Custom sizes: 5.5 x 7.17 in. to 11.69 x 17 in. / 139.7 x 182.0 mm to 297.0 x 431.8 mm
Weights	16 lb. bond to 95 lb. cover / 60 to 256 gsm
Types	<ul style="list-style-type: none"> Bond Plain Paper Cardstock Custom Hole Punched Labels Heavyweight Labels Extra Heavyweight Labels Letterhead Lightweight Cardstock Lightweight Glossy Cardstock Lightweight Glossy Cardstock Reload Heavyweight Cardstock Pre-Printed Recycled

Xerox® VersaLink® C7020/C7025/C7030 Color Multifunction Printer

High Capacity Tandem Tray Module (Optional)	
Capacity ⁴	Tray 2: 520 sheets Tray 3: 870 sheets Tray 4: 1,130 sheets
Sizes	Tray 2: Custom sizes: 5.5 x 7.17 in. to 11.69 x 17 in. / 139.7 x 182.0 mm to 297.0 x 431.8 mm Tray 3: Standard Sizes: 8.5 x 11 in. and 7.25 x 10.5 in. / A4 or B5 Tray 4: Standard Sizes: 8.5 x 11 in. and 7.25 x 10.5 in. / A4 or B5
Weights	16 lb. bond to 95 lb. cover / 60 to 256 gsm
Types	Bond Plain Paper Cardstock Custom Hole Punched Labels Heavyweight Labels Extra Heavyweight Labels Letterhead Lightweight Cardstock Lightweight Glossy Cardstock Lightweight Glossy Cardstock Reload Heavyweight Cardstock Pre-Printed Recycled
Envelope Tray – Replaces Tray 1 (Optional)	
Capacity ⁴	Up to 60 envelopes
Sizes	#10 commercial, Monarch, DL, C5 Custom sizes: 3.9 x 5.8 in. to 6.4 x 9.5 in. / 98 x 148 mm to 162 x 241 mm
Weights	20 lb. bond to 25 lb. bond / 75 to 90 gsm
High Capacity Feeder (Optional)	
Capacity ⁴	2,000 sheets
Sizes	Standard Sizes: 8.5 x 11 in. and 7.25 x 10.5 in. / A4 or B5
Weights	16 lb. bond to 80 lb. cover / 60 to 216 gsm
Total Capacity	
Base Unit Capacity ⁴	620 sheets
Single Tray Module Capacity ⁴	1,140 sheets
Single Tray Module with Stand Capacity ⁴	1,140 sheets
Three Tray Module Capacity ⁴	2,180 sheets
High-Capacity Tandem Tray Capacity ⁴	3,140 sheets
Finishing	
Output Trays (Optional on Base Model)	
Dual Catch Trays ⁴	250 sheets each; Lower tray offsets
Integrated Office Finisher (Optional)	
Stacking Tray	500 sheets of 20 lb. bond / 80 gsm – 8.5 x 11 in. / A4 or 250 sheets of 20 lb. bond / 80 gsm – 11 x 17 in. / A3
Sizes	3.5 x 3.9 in. to 11.7 x 17 in. / 89 x 98 mm to 297 x 432 mm
Weights	16 lb. bond to 80 lb. cover / 60 to 220 gsm

Xerox® VersaLink® C7020/C7025/C7030 Color Multifunction Printer

Stapling	Single Auto stapling: 50 sheets maximum: Letter / A4 / B5-size sheets (less than 90 gsm or (2) 220 gsm covers) 30 sheets maximum: Legal / Tabloid / A3 / B4-size sheets (less than 90 gsm or (2) 220 gsm covers)
Office Finisher LX (Optional)	
Capacity⁴	Stacking Tray: 2,000 sheets unstapled or 1,000 sheets single stapled or 750 sheets dual stapled (8.5 x 11 in. / A4) (dual stapling only with optional booklet maker)
Sizes	8.3 x 7.2 in. to 11.7 x 17 in. / 210 x 182 mm to 297 x 432 mm
Weights	16 lb. bond to 80 lb. cover / 60 to 220 gsm
Multiposition Stapling	50 sheets of 24 lb. bond / 90 gsm
Hole Punch (Optional) North America: Europe:	2-3 Hole Punch 2-4 Hole Punch
Booklet Maker for Office Finisher LX (Score/Crease, Saddle-stitch Staple) (Optional)	
Capacity⁴	40 booklets (2-15 sheets per booklet – 20 lb. / 80 gsm or less)
Sizes	Letter – 8.5 x 11 in. / A4 SEF Legal – 8.5 x 14 in. / B4 SEF Ledger – 11 x 17 in. / A3 SEF
Saddle-stitch Stapling	2-15 sheets / 8-60 page booklet 16 lb. bond to 24 lb. bond / 60 to 90 gsm
Score / Crease	1-15 sheets / unstapled
Convenience Stapler and Work Surface (Optional)	
Capacity⁴	50-sheet stapling 5,000 staples Requires a separate outlet
Device Management	
Network Protocols	TCP/IP: HTTP/HTTPS, Internet Printing Protocol, LPR/LPD, Raw Socket Printing/Port 9100, IPv4/IPv6, WSD LDAP Bonjour® / AirPrint™ FTP Most protocols not in use can be disabled
Administrative Protocols	DHCP, SNMP, WINS, HTTP, HTTPS, TLS, SNTP, MDNS
Xerox® CentreWare® Web	
	<ul style="list-style-type: none"> • A Web-based server application for network administrators that permits web browser-based device management from any workstation, whether running Windows or UNIX or any other operating system • Works with any SNMP-managed printer from any manufacturer • Provides help with device discovery and installations, health checks and troubleshooting, and device upgrades, as well as basic accounting and asset management
Embedded Web Server – Integrated Device Web Page	
Device Status	Web server embedded <ul style="list-style-type: none"> • Tray status/contents • Consumables status • Billing/Usage • Quick Links
Print Queue Viewing	Job print queue management—view and delete
Job Submission	Print-ready files (PS (with optional PostScript option), PCL, PDF, XPS, JPEG)
Device Administration	Allows simple, remote installation setting of configuration options and management of the device

Xerox® VersaLink® C7020/C7025/C7030 Color Multifunction Printer

Browsers	Microsoft® Internet Explorer® 11 Microsoft Edge™ 38 Mozilla™ Firefox® 48 Apple® Safari® 9.1 Google Chrome™ 52	
Remote Services		
Xerox® Meter Assistant® Service	Automates the process of collecting and submitting meter reads for tracking and billing of Xerox® device usage. Eliminates the need for time-consuming end-user involvement and ensures that meter reads are submitted to Xerox on time.	
Xerox® Supplies Assistant® Service	Automatically orders supplies for Xerox® output devices based on actual usage, eliminating the need to manually manage supplies inventory.	
MaintenanceAssistant	Offers a fast (and free) way to resolve potential issues and receive assistance and automate the troubleshooting/repair process. Diagnostic data is sent to Xerox, allowing for problems to be solved faster with increased uptime.	
Supplies and Accessories	Quantity	Part Number
Supplies		
High Capacity Print Cartridges	Cyan: 9,800 standard pages ⁶ Magenta: 9,800 standard pages ⁶ Yellow: 9,800 standard pages ⁶ Black: 16,100 standard pages ⁶	106R03744 106R03743 106R03742 106R03741
Extra High Capacity Print Cartridges	Cyan: 16,500 standard pages ⁶ Magenta: 16,500 standard pages ⁶ Yellow: 16,500 standard pages ⁶ Black: 23,600 standard pages ⁶	106R03740 106R03739 106R03738 106R03737
Metered Print Cartridges	Cyan: 15,000 standard pages ⁷ Magenta: 15,000 standard pages ⁷ Yellow: 15,000 standard pages ⁷ Black: 22,000 standard pages ⁷	106R03736 106R03735 106R03734 106R03733
Drum Cartridge	Black: 109,000 ⁸ Cyan, Magenta, Yellow : 87,000 standard pages ⁸	113R00780
Waste Toner Bottle	30,000	115R00128
LX Booklet Maker Cartridge (8 cartridges per container)	16,000 staples (2,000 each cartridge)	008R12897
Staple Refills for Finishers (3 refills per container)	15,000 staples (5,000 each refill)	008R12941
Staple Cartridge for Finishers (1 cartridge per container)	5,000 staples (5,000 each cartridge)	008R12964

Xerox® VersaLink® C7020/C7025/C7030 Color Multifunction Printer

Accessories / Options	
Single Tray Module (does not include stand – for Desktop Model only)	097S04910
Single Tray with Stand Module	097S04907
Three Tray Module	097S04908
High-Capacity Tandem Tray Module	097S04909
Envelope Tray (Replaces Tray 1)	497K17720
Center Output Tray (Dual Catch Tray) (Optional on Desktop Model)	497K17800
HDD (320 GB hard drive) (Optional on Desktop Model)	497K17740
1 Line Fax Kit (PSTN Fax)	497K17750
3 Line Fax Kit (PSTN Fax)	497K17760
Wireless Network Adapter Kit	497K16750
Internal Card Reader / RFID Kit	497K18120
PostScript Kit	497K18340
Fax Over IP Kit	497K18330

¹ Maximum volume capacity expected in any one month. Not expected to be sustained on a regular basis.

² Expected regular monthly throughput.

³ Requires analog phone line.

⁴ Paper capacities are based on 20 lb. / 75 gsm stock; capacities will vary with different weight stocks.

⁵ Power states defined per ENERGY STAR® Program requirements for Imaging Equipment.

⁶ Average standard pages. Declared Yield in accordance with ISO/IEC 19798. Yield will vary based on image, area coverage and print mode.

⁷ Assumptions: Toner cartridge yield is based on 5% area coverage on 8.5 x 11 in. / A4 LEF. Toner yield can vary due to many factors, including but not limited to, image area coverage, image content, media size, run mode, application types, monthly print volumes and image quality set-points.

⁸ Approximate pages. Declared yield will vary depending on job run length, media size/orientation and machine speed. For more information visit: <http://www.office.xerox.com/latest/SUPGL-01.pdf>.

Return spent imaging supplies through the Xerox Green World Alliance collection/reuse/recycling program. For more information, visit www.xerox.com/about-xerox/recycling.

For more information, visit us at www.xerox.com/office

Configurations vary by geography.