

Xerox® Color C60/C70 Printer

Color Multifunction Printer

To interactively build and configure your own Xerox® Color C60/C70, please visit www.buildyourownxerox.com.



Xerox® Color C60 Printer		Xerox® Color C70 Printer		
Simplex Speeds	Color	Black-and-white	Color	Black-and-white
8.5 x 11 in. / A4 60 to 105 gsm uncoated 106 to 176 gsm uncoated 106 to 150 gsm coated 151 to 300 gsm uncoated 151 to 300 coated	Up to 60 ppm Up to 43 ppm Up to 43 ppm Up to 30 ppm Up to 30 ppm	Up to 65 ppm Up to 65 ppm Up to 43 ppm Up to 43 ppm Up to 30 ppm	Up to 70 ppm Up to 50 ppm Up to 50 ppm Up to 35 ppm Up to 35 ppm	Up to 75 ppm Up to 75 ppm Up to 50 ppm Up to 50 ppm Up to 35 ppm
11 x 17 in. / A3 60 to 105 gsm uncoated 106 to 176 gsm uncoated 106 to 150 gsm coated 151 to 300 gsm uncoated 151 to 300 coated	Up to 30 ppm Up to 21 ppm Up to 21 ppm Up to 14 ppm Up to 14 ppm	Up to 33 ppm Up to 33 ppm Up to 21 ppm Up to 21 ppm Up to 14 ppm	Up to 35 ppm Up to 25 ppm Up to 25 ppm Up to 17 ppm Up to 17 ppm	Up to 37 ppm Up to 37 ppm Up to 25 ppm Up to 25 ppm Up to 17 ppm
12 x 18 in. / SRA3 60 to 105 gsm uncoated 106 to 176 gsm uncoated 106 to 150 gsm coated 151 to 300 gsm uncoated 151 to 300 coated	Up to 27 ppm Up to 19 ppm Up to 19 ppm Up to 12 ppm Up to 12 ppm	Up to 29 ppm Up to 29 ppm Up to 19 ppm Up to 19 ppm Up to 12 ppm	Up to 30 ppm Up to 19 ppm Up to 19 ppm Up to 12 ppm Up to 12 ppm	Up to 33 ppm Up to 33 ppm Up to 19 ppm Up to 19 ppm Up to 12 ppm
Auto Duplex Speeds	Color	Black-and-white	Color	Black-and-white
8.5 x 11 in. / A4 Example: 60 to 105 gsm uncoated	Up to 60 ipm 2-sided 30 sheets per minute	Up to 65 ipm 2-sided 32 sheets per minute	Up to 70 ipm 2-sided 35 sheets per minute	Up to 75 ipm 2-sided 35 sheets per minute
11 x 17 in. / A3 Example: 60 to 105 gsm uncoated	Up to 30 ppm 2-sided 15 sheets per minute	Up to 33 ppm 2-sided 16 sheets per minute	Up to 35 ppm 2-sided 17 sheets per minute	Up to 37 ppm 2-sided 18 sheets per minute
Device Specifications				
Monthly Duty Cycle	Up to 300,000 pages (maximum volume capacity expected in any one month, not expected to be sustained on a regular basis). ¹			
Average Monthly Print Volume (AMPV)	10,000 to 50,000 pages per month ²			
Technology	Xerox® EA toner with Ultra Low Melt Technology (2400 x 2400 dots per inch)			
Control Panel Languages	International English, International French, Italian, German, International Spanish, Dutch, Brazilian Portuguese, Swedish, Norwegian, Danish, Finnish, Turkish, Greek, Russian, Czech, Polish, Hungarian, Romanian, Catalan			

Xerox® Color C60/C70 Printer

Accessories			
Optional	Offset Catch Tray High Capacity Feeder (A4) 1 Tray Oversized High Capacity Feeder with Storage Bin 2 Tray Oversized High Capacity Feeder Interface Module BR Finisher (includes Vertical Transport Kit) BR Booklet Maker Finisher (includes Vertical Transport Kit) C Fold / Z Fold Unit for BR Finisher or BR Booklet Maker Finisher Standard Finisher (requires Interface Module) Standard Finisher with Booklet Maker (requires Interface Module) C/Z Folder for Standard Finisher (requires Interface Module and Standard Finisher with or without Booklet Maker) GBC® AdvancedPunch™ (requires Interface Module and Standard Finisher with or without Booklet Maker) GBC® AdvancedPunch™ PRO (requires Interface Module and Standard Finisher with or without Booklet Maker) Xerox® SquareFold® Trimmer Module (requires Interface Module and Standard Finisher with Booklet Maker) Convenience Stapler Xerox® EX-i C60/C70 Print Server Powered by Fiery® Xerox® FreeFlow Print Server Integrated for the Xerox® Color C60/C70 Printer Xerox® EX C60/C70 Print Server Powered by Fiery® Foreign Device Interface Kit Mobility Plate Envelope Fuser Kit USB Hub XMPie® Variable Data Printing PostScript Kit (recommended for Xerox® Integrated Color Server for the Xerox® Color C60/C70 – PostScript Kit not used with Fiery or FreeFlow Print Servers) Media Card Reader VOIP Fax 1 (3 Line Outside N. America) Fax Kits Server Fax Kit Common Access Card Enablement Kit Xerox® Scan to PC Desktop® Equitrac Office®		
Electrical Requirements			
North America	Voltage: 110-127V Frequency: 50/60 Hz +/- 3%, 20 A		
Europe	Voltage: 220-240V Frequency: 50/60 Hz +/- 3%, 10 A		
Accessories North America: Europe:	Each module requires 120V, 15 A Each module requires 220V, 10 A		
Power Consumption			
Running (Average)	C60: 1,052 watts; C70: 1,250 watts		
Sleep Mode (Average)	3 watts (Default time to Sleep mode = 2 min.)		
Low Power Mode Recovery Time	Less than 20 seconds		
Operating Environment			
Required Temperature Range	50° to 82° F / 10° to 28° C (Relative Humidity less than 62.5% when temp is 32° C or less)		
Required Relative Humidity	15% to 85% (no condensation)		
Sound Power Levels	Operating: 6.8 B(A); Standby: 3.6 B(A)		
Sound Pressure Levels	Operating: 56 dB(A); Standby: 18 dB(A)		
Weight (approximate base unit only)	604 lb., 273 kg		
Dimensions	Width	Depth	Height
Base Unit with Offset Catch Tray	62 in. / 1,574 mm	31.6 in. / 803.5 mm	54.8 in. / 1,391.5 mm
Base Unit with BR Finisher	79.1 in. / 2,009 mm	31.6 in. / 803.5 mm	54.8 in. / 1,391.5 mm
Base Unit with BR Booklet Maker Finisher	81.4 in. / 2,068 mm	31.6 in. / 803.5 mm	54.8 in. / 1,391.5 mm
Base Unit with BR Booklet Maker Finisher and C Fold / Z Fold Unit	90.6 in. / 2,301 mm	31.6 in. / 803.5 mm	54.8 in. / 1,391.5 mm
Base Unit with Standard Finisher	97.7 in. / 2,481 mm	31.6 in. / 803.5 mm	54.8 in. / 1,391.5 mm
Base Unit with Booklet Maker Finisher	122.9 in. / 3,121.7 mm	31.6 in. / 803.5 mm	54.8 in. / 1,391.5 mm
GBC® AdvancedPunch™	12 in. / 305 mm	28.5 in. / 724 mm	38.5 in. / 978 mm
GBC® AdvancedPunch™ PRO	17.5 in. / 445 mm	28.5 in. / 724 mm	39 in. / 992 mm

Xerox® Color C60/C70 Printer

Xerox® SquareFold® Trimmer	42 in. / 1,066.3 mm	28.5 in. / 724 mm	22 in. / 558.8 mm
High Capacity Feeder	15.3 in. / 389 mm	24.2 in. / 614 mm	14.8 in. / 377 mm
One Tray Oversized High Capacity Feeder	38.9 in. / 988 mm	30.0 in. / 762 mm	39.1 in. / 992 mm
Two Tray Oversized High Capacity Feeder	38.9 in. / 988 mm	30.0 in. / 762 mm	39.1 in. / 992 mm
Certifications			
	WHQL certification (depending on print server / controller selected) Citrix MEDITECH SAP Common Criteria Certification ENERGY STAR® Environmental Choice EPEAT GS Mark NOM EAC/GOST To view the latest list of certifications, go to www.xerox.com/OfficeCertifications .		
Graphic Arts Credentials			
	FOGRA certification* PANTONE® Matching System* PANTONE GOE* PANTONE PLUS* Adobe® PDF Print Engine* Adobe® PostScript® 3™ (certified) IDEAlliance Digital Press Certified to GRACoL® specifications *requires an additional Print Server option		
Paper Handling			
Single-pass Automatic Document Feeder			
Capacity³	250 sheets of plain paper – 20 lb. / 75 gsm		
Speed	Up to 200 ipm color / 200 ipm black-and-white (2-sided, 8.5 x 11 in. / A4)		
Paper Sizes	Custom sizes: 5.5 x 8.5 in. to 11 x 17 in. / A5 to A3		
Weights	16 to 53 lb. bond / 38 to 200 gsm		
Bypass Tray			
Capacity³	Up to 250 sheets		
Sizes	Custom sizes: 4 x 6 in. to 13 x 19 in. / 102 x 152 mm to 330.2 x 482.6 mm (A5 to SRA3)		
Weights	18 lb. bond to 110 lb. cover / 64 to 300 gsm (uncoated and coated)		
Envelope Capacity	30 to 50 envelopes		
Envelope Sizes	#10 Commercial, Monarch (including custom size), C4, C5 (Available as Tray 5. Paper Size Default within tools) run flap open at the trail edge) Custom sizes: 7.5 x 6.7 in. to 9.45 x 6.81 in. / 190 x 170 mm to 240 x 173 mm Digital Laser envelopes recommended		
Envelope Weights	75 to 90 gsm		
Trays 1 to 4			
Capacity³	Tray 1: 500 sheets Tray 2: 500 sheets Tray 3: 870 sheets Tray 4: 1,140 sheets		
Sizes	Tray 1: 5.5 x 8.5 in. to 12 x 18 in. / A5 to SRA3 Tray 2: 5.5 x 8.5 in. to 11 x 17 in. / A5 to A3 Tray 3: 7.25 x 10.5 in., 8.5 x 11 in. / B5, A4 Tray 4: 7.25 x 10.5 in., 8.5 x 11 in. / B5, A4		
Weights	Trays 1 and 2: 16 lb. bond to 96 lb. cover / 60 to 256 gsm (uncoated and coated) Trays 1 and 2: Up to 256 gsm (uncoated) Trays 3 and 4: 16 lb. bond to 80 lb. cover / 60 to 220 gsm (uncoated and coated)		
Optional High Capacity Feeder (HCF)			
Capacity³	2,000 sheets		
Sizes	7.25 x 10.5 in., 8.5 x 11 in. / 184.2 x 266.7 mm, 279.4 x 215.9 mm (B5, A4)		
Weights	16 lb. bond to 60 lb. cover / 64 to 220 gsm (uncoated and coated)		

Optional Oversized High Capacity Feeder (OHCF) – 1 or 2 Tray Options	
Capacity³	1 Tray OHCF: 2,000 sheets plus Storage Cabinet 2 Tray OHCF: 4,000 sheets
Sizes	1 Tray OHCF: 7.2 x 10 in. / 182 x 250 mm (B5) to 13 x 19.2 in. / 330 x 488 mm (SRA3) 2 Tray OHCF: 4 x 6 in. / 102 x 152 mm to 13 x 19.2 in. / 330 x 488 mm (SRA3)
Weights	16 lb. bond to 110 lb. cover / 60 to 300 gsm (uncoated and coated)
Total Capacity	
Standard Capacity	3,260 sheets (includes Bypass Tray and Trays 1-4)
Maximum Capacity	7,260 sheets (includes Bypass Tray, Trays 1-4 and Two-tray Oversized High Capacity Feeder)
Automatic Two-Sided	<ul style="list-style-type: none"> • 94 lb. cover / 256 gsm auto duplex • 110 lb. cover / 300 gsm manual duplex for all stocks from bypass trays and optional Oversized High Capacity Feeder
Finishing	
Offset Catch Tray	
Capacity³	500-sheet stacking
Optional BR Finisher (Requires Vertical Transport Kit)	
Capacity³	Offsetting Top Tray: 500 sheets Stacking Stapling Tray: 3,000 sheets unstapled or 100 sets (dual or 4-position staple) 11x17 in., 8.5 x 14 in., A3 or 200 sets (single-position staple) 8.5 x 11 in. / A4
Sizes	4 x 6 in. to 12 x 19 in. / A6 to SRA3 for stacking 7.25 x 10.5 in. to 11 x 17 in. / B5 to A3 for stapling 5.5 x 8.5 in. / A5 output to top tray; punch and offset
Weights	16 lb. bond to 110 lb. cover / 64 to 300 gsm (coated and uncoated)
Stapling	Single and multiposition stapling Auto stapling (50 sheets maximum) – 24 lb/90 gsm Letter, Legal, Tabloid, A3, A4, B4 and B5 sizes supported
Hole Punch North America: Europe:	2-3 Hole Punch 2-4 Hole Punch 4 Hole Swedish Punch (Optional)
Optional BR Booklet Maker Finisher (Requires Vertical Transport Kit)	
Capacity³	Offsetting Top Tray: 500 sheets of 8.5 x 11 in. / A4 unstapled Stacking Stapling Tray: 1,500 sheets of 8.5 x 11 in. / 11 x 17 in. / A4 / A3 / SRA3 unstapled or 200 stapled sets of 8.5 x 11 in. / A4 (single-position stapling or dual or 4-position stapling) or 100 stapled sets of 11 x 17 in. / A3 / SRA3
Sizes	4 x 6 in. to 12 x 19 in. / A6 to SRA3 for stacking 7.25 x 10.5 in. to 11 x 17 in. / B5 to A3 for stapling 5.5 x 8.5 in. / A5 output to top tray; punch and offset
Weights	16 lb. bond to 110 lb. cover / 64 to 300 gsm (coated and uncoated)
Stapling	Single and multiposition stapling Auto stapling (50 sheets maximum) – 24 lb/90 gsm Letter, Legal, Tabloid, A3, A4, B4 and B5 sizes supported
Hole Punch North America: Europe:	2-3 Hole Punch 2-4 Hole Punch 4 Hole Swedish Punch (Optional)
Booklet Maker	Saddle-stitch 2 to 16 sheets (7 sheets at 106 to 176 gsm coated or 5 sheets at 177 to 220 gsm coated) Bi-fold up to 5 sheets Letter, Legal, Tabloid, A3, A4, 12 x 18 in., SRA3 supported
Optional C Fold / Z Fold Unit (Optional with BR Finisher and BR Booklet Maker Finisher)	
Types	C Fold, Z Fold and Z Half Fold
Capacity³	40 sheets
Sizes	C Fold and Z Fold: Letter – 8.5 x 11 in. / A4 SEF only Z Half Fold: Tabloid – 11 x 17 in. / A3 only
Weights	16 lb. to 24 lb. bond / 64 to 90 gsm

Xerox® Color C60/C70 Printer

Output Tray	Envelope Tray: C Fold, Z Fold and Tri-fold Stacker Tray or Top Tray: Z Half Fold
Optional Standard Finisher (requires Interface Module)	
Capacity	Top Tray: 500 sheets of 20 lb. bond / 80 gsm, 8.5 x 11 in. / A4 Lower Tray: 3,000 sheets of 20 lb. bond / 80 gsm, 8.5 x 11 in. / A4
Sizes	4 x 6 in. to 13 x 19 in. / A6 to SRA3
Weights	18 lb. bond to 110 lb. cover / 64 to 300 gsm
Multiposition Stapling	Up to 100 sheets of 20 lb. bond / 80 gsm
Hole-punching North America: Europe:	2-3 Hole Punch 2-4 Hole Punch 4 Hole Swedish Punch (Optional)
Interposing Capacity Capacity: Sizes: Weights:	200 sheets of 128 gsm 5.5 x 8.5 in., 8 x 10 in., 8.5 x 11 in., 8.5 x 14 in., 8.5 x 12.5 in., 11 x 15 in., 11 x 17 in. / A3, A4, B4, B5 18 lb. bond to 80 lb. cover / 64 to 220 gsm
Decurling	Included with Interface Module and Standard Finisher Bidirectional with Auto and Manual settings
Optional Standard Finisher with Booklet Maker (requires Interface Module)	
Capacity	Top Tray: 500 sheets of 20 lb. bond / 80 gsm, 8.5 x 11 in. / A4 Lower Tray: 2,000 sheets of 20 lb. bond / 80 gsm, 8.5 x 11 in. / A4
Sizes	4 x 6 in. to 13 x 19 in. / A6 to SRA3
Weights	18 lb. bond to 110 lb. cover / 64 to 300 gsm
Multiposition Stapling	Up to 100 sheets of 20 lb. bond / 80 gsm
Hole-punching North America: Europe:	2-3 Hole Punch 2-4 Hole Punch 4 Hole Swedish Punch (Optional)
Interposing Capacity Capacity: Sizes: Weights:	200 sheets of 128 gsm 5.5 x 8.5 in., 8 x 10 in., 8.5 x 11 in., 8.5 x 14 in., 8.5 x 12.5 in., 11 x 15 in., 11 x 17 in. / A3, A4, B4, B5 18 lb. bond to 80 lb. cover / 64 to 220 gsm
Decurling	Included with Interface Module and Standard Finisher Bidirectional with Auto and Manual settings
Booklet Making Capacity	Saddle-stitch 2 to 25 sheets of 79 gsm (uncoated) Bi-fold up to 5 sheets 8.5 x 11 in., 8.5 x 13 in., 8.5 x 14 in., 9 x 11 in., 11 x 15 in., 11 x 17 in., 12 x 18 in., 13 x 18 in. / A4, B4, A3, SRA3
Optional GBC® AdvancedPunch (Optional with Standard Finisher – requires Interface Module)	
Punch Configuration Sizes	8.5 x 11 in. / 216 x 279 mm to 13 x 19.2 in. / 330 x 488 mm
Weights	20 lb. bond to 80 lb. cover / 75 to 216 gsm (uncoated and coated)
	Wide selection of slide-in / slide-out GBC punch die sets available
Optional GBC® AdvancedPunch PRO (Optional with Standard Finisher with or without Booklet Maker – requires Interface Module)	
Punch Configuration Sizes	5.5 x 8.5 in. / 148 x 210 mm (A5) LEF to 13 x 19.2 in. / 330 x 488 mm (SRA3) SEF
Weights	20 lb. bond to 110 lb. cover / 75 to 300 gsm (uncoated); 28 lb. bond to 110 lb. cover / 106 to 300 gsm (coated)
	Wide selection of slide-in / slide-out GBC punch die sets available
Optional Xerox® SquareFold® Trimmer Module (Optional with Standard Finisher – requires Interface Module)	
Capacity	5 to 20-sheet booklets (up to 80 imaged sides) at 24 lb. / 90 gsm 5 to 25-sheet booklets (up to 100 imaged sides) at 20 lb. / 80 gsm
Sizes	Custom sizes: 8.5 x 11 in. to 13 x 18 in. / A4 to SRA3
Weights	18 lb. bond to 110 lb. cover / 64 to 300 gsm
Convenience Stapler	
Capacity	50 sheets (24 lb. / 90 gsm media)
Print	
Print Resolution	Up to 2400 x 2400 dpi
Line Screens	600, 300, 200 and 150 Clustered Dot, 200 Rotated Line Screen (depending on print server / controller selected)

Xerox® Color C60/C70 Printer

Registration	<ul style="list-style-type: none"> Advanced registration technology for tighter control Simple Image Quality Adjustment (SIQA) for de-skew, registration and density uniformity (Available on all configurations) + 1.2 mm front to back registration
First-print-out Time	PS- A4 LEF Simplex Color 10.4 seconds / Black-and-white 8.5 seconds
Print Features	<ul style="list-style-type: none"> A true multifunction product – print, copy, fax and scan, including scan to PC, USB or email, and mobile printing Benchmark image quality with 2400 x 2400 dpi resolution and EA low melt toner for a smooth, offset-like finish Makes mobile printing simpler and more convenient Expansive media range lets you print everything from postcards to posters, both coated and uncoated stock, up to 300 gsm Xerox Extensible Interface Platform® (EIP) allows you to connect to third-party software solutions that you can access from the touch-screen of the device Your choice of servers to best fit your environment: <ul style="list-style-type: none"> Xerox® Integrated Color Server for the Xerox® Color C60/C70 Printer Xerox® EX-i C60/C70 Print Server Powered by Fiery® Xerox® FreeFlow® Print Server Integrated for the Xerox® Color C60/C70 Printer Xerox® EX C60/C70 Print Server Powered by Fiery® Inline finishing options offer a professional polish with stapling, hole-punching, folding and booklet making for presentations, brochures, reports and newsletters Be secure with integrated security features such as IP filtering, image overwrite, secure print, encrypted Scan to Email, authentication and IPv6 support
Xerox® Mobile Express Driver®	Makes it easy for mobile users to find, use and manage Xerox® and non-Xerox devices in every new location. Plug into a new network and Mobile Express Driver automatically discovers available printers and provides status and capability information. Save a list of “favorite” printers for each location, store application print settings for use on any printer in any network, and greatly reduce mobile support calls to IT.
Xerox® Global Print Driver®	A truly universal print driver that lets IT administrators install, upgrade and manage Xerox® and non-Xerox devices from a single driver. It provides a consistent, easy-to-use interface for end-users, reducing the number of support calls, and simplifying print services management.
Print Solutions	
Xerox® Mobile Print Cloud (Optional)	Xerox® Mobile Print Cloud addresses the needs of businesses with a mobile workforce and puts you ahead of the evolving mobile print need, but without burdening staff, budget or infrastructure. Getting started takes only a few minutes via the cloud. Print from any mobile device to nearly any brand of printer. Accurate printing with true Microsoft® Office® rendering and more. Print what you need, when, where and how you need it.
Xerox® Mobile Print Solution (Optional)	Xerox® Mobile Print Solution is an ideal choice for sites that have additional requirements for control and security with an onsite server. Xerox® Mobile Print Solution allows users to print from most mobile devices to nearly any brand of printer or multifunction printer without drivers or added complexity. Simply enter a release code (PIN) at the device and get accurate printing with true Microsoft Office rendering and more to use with your server for private, onsite deployment.
Copy	
First-copy-out Time From the Platen: From the DADF:	As fast as 7.8 seconds color / 5.1 seconds black-and-white As fast as 9.6 seconds color / 5.3 seconds black-and-white
Warm Up Time	90 seconds (from cold powered down to Ready Copy)
Digital Imaging	Auto color Auto rotation Image shift Edge erase Auto centering Original type selection (photo and text, photo, text, map) with subtypes Lighter/darker Background suppression Auto and manual contrast Sharpness Color balance, color shift and saturation
Reduce / Enlarge	Variable zoom from 25% to 400% in 1% increments Anamorphic zoom Six user-programmable percentages

Xerox® Color C60/C70 Printer

Special Features	<p>Auto paper select Auto reduction/enlargement to fit selected paper size Auto tray switching Automatic job recovery Auto color selection Area Designation Poster mode Annotation Single/Dual color Booklet creation Multi-up – 2, 4 or 8 up Repeat Image Negative image Mirror image Covers insertion (front only, front and back, back only, blank or printed) Build Job (enables special programming for different pages in one document – can be used for inserts, different paper sources and mixing input from the document glass and the document feeder) Job interrupt Book copying Sample job Mixed-size originals Sheet Insert Stamping 2-in-1 X Y Zoom Zoom Range 25 to 400% Margin Shift Photo Mode Poster Mode Preset Reduce / Enlarge Program Ahead Covers Erase, Image Repeat, Image Rotate Interrupt Job Build Job Program</p>
Scan	
Concurrency	Scan while printing or while it is transferring scan to network or fax jobs
Scan Features	<p>Mixed size originals Edge erase Reduction/enlargement Fit to size Scan Build Job Compression Quality / File Size Control Original type (photo and text, photo, text) Auto Background and Shadow Suppression Job Flow Sheets Thumbnail Preview Scan to USB (optional) Preview scan job</p>
Input Speed	Up to 200 images per minute color and black-and-white
Resolution	<p>600 x 600 dpi 400 x 400 dpi 300 x 300 dpi 200 x 200 dpi</p>
Maximum Scan Area	Originals up to 11 x 17 in. / A3
Network Print Services	<p>Novell NDPS Novell Pserver / NDS Port 9100 RFC 1179 (LPR) Print to Mailbox and Release</p>
File Formats	<p>PDF Image Only PDF (Searchable) PDF (Linearized) PDF (A-1 Level A) TIFF V6 JFIF XPS</p>
Document Management Fields (Metadata)	<p>One to six user-programmable metadata fields per scan job Customized fields viewed on user interface Variable data entered using virtual keyboard</p>

Xerox® Color C60/C70 Printer

Scan Features	<p>Scan to Home Scan to Desktop WIA Scan to Desktop TWAIN Scan to Mailbox Scan to FTP Scan to sFTP Scan via NDS Scan via SMB Scan via HTTP Scan via HTTPS Scan to USB Storage Device Scan to Remote Printer Scan to Fax Server Scan to Multiple Destinations Scan to Documentum Scan to DocuShare Scan to Domino Scan to Hummingbird Scan to Interwoven WorkSite Scan to Live Link Enterprise Server Scan to Microsoft Dynamics GP Scan to MS Exchange web folder Scan to Microsoft SharePoint Scan to SharePoint Portal Server Scan to Thompson ProLaw Scan to Tower TRIM Scan to Web URL Scan to Microsoft Network Folder Scan to Exact e-Synergy</p>
Supported Scan Destinations (Standard)	Scan to Email, Scan to Folder, to PC, to Mailbox (private and public), Scan to USB, FTP, SMB, Desk, Text searchable PDF, PDF/A, XPS, Thumbnail Preview
Scan to Email Features	<p>Color scanning, Auto Color, Grayscale, Black-and-white Direct document email from device Manual or directory Exchange / Notes / LDAP address searching Signing and encryption Email over SSL Preview scan job</p>
Authentication	<p>SMTP authentication, POP before SMTP, APOP, System credentials Single sign on (LDAP, SMB, Kerberos authentication)</p>
Fax (Optional) – One or Three Line Fax Options	
Compatibility	Color, Auto Color, Black-and-white
Maximum Scan Area	11 x 17 SEF
Fax Send Features	<p>iFax Lan Fax IP Fax Fax Forward to Email Fax Forward to FTP destination Fax Forward to SMB destination Fax Forward to Fax destination</p>
Fax Print Features	<p>Print from USB Storage Device Media Print Unicode Printing</p>
Fax Features	<p>iFax Lan Fax IP Fax Fax Forward to Email Fax Forward to FTP destination Fax Forward to SMB destination Fax Forward to Fax destination</p>
Device Management	
Xerox® CentreWare® Internet Services – Integrated Web Pages Provided by the Device	
Device Status	<p>Web server embedded in Network Controller:</p> <ul style="list-style-type: none"> • Tray status/contents • Consumables status • Alerts
Job Submission	<p>Print ready files: PS, PCL, TIFF, PDF, JPG, XPS Output feature selection (2-sided, output color, collate, orientation, staple, hole punch, folding, output destination) Delivery options (Immediate, sample set, delay and secure, Save job or reprint)</p>
Device Administration	Allows simple, remote installation setting of configuration options and management of the device

Xerox® Color C60/C70 Printer

Browsers	Internet Explorer 7.x, 8.x, 9.x Safari 5.x Mozilla Firefox 4.x, 5.x, 6.x, 7.x, 8.x, 9.x, 10.x, 11.x Opera 11.x Chrome 12
Support	Install print / scan drivers and online support available via web page
Languages Supported	International English, International French, Italian, German, International Spanish, Dutch, Brazilian Portuguese, Swedish, Norwegian, Danish, Finnish, Russian, Simplified Chinese, Korean, Japanese
Remote Services	
Xerox® MeterAssistant®	Automates the process of collecting and submitting meter reads for tracking and billing of Xerox® device usage. Eliminates the need for time-consuming end-user involvement and ensures that meter reads are submitted to Xerox on time.
Xerox® SuppliesAssistant®	Automatically orders supplies for Xerox® output devices based on actual usage, eliminating the need to manually manage supplies inventory.
Xerox® MaintenanceAssistant	Offers a fast (and free) way to resolve potential issues and receive assistance and automate the troubleshooting / repair process. Diagnostic data is sent to Xerox, allowing for problems to be solved faster with increased uptime.
Security	
Features	Secure Print IPsec HTTPS (SSL) Embedded Fax Port Blocking IPv6 Support IPv4 and IPv6 Environments OS Security Updates 802.1X Support (IEEE Standard) Secure Login Network Authentication IP Address Restriction Job Audit Tray Data Encryption 128-bit AES Encryption 256-bit AES Encryption Image Overwrite Common Criteria Certification
Print Server	
Xerox® Integrated Color Server for the Xerox® Color C60/C70 Printer	
Processor	1.0 GHz Dual-core
Memory	4 GB system plus 1 GB page memory
System Disk	320 GB Hard Disk Drive
Display	10.4 in. color touchscreen flat-panel
Device Operating System	VxWorks
PDLS Page Description Languages	Adobe® PostScript® 3™ PDF PCL® 5c, 6 XML Paper Specification (XPS®) (optional)
Operating Systems	Windows® XP Windows Server 2003 (32- and 64-bit) Windows Server 2008 (32- and 64-bit) Windows Server 2012 Windows Vista (32- and 64-bit) Windows 7 (32- and 64-bit) Windows 8 (32- and 64-bit) Mac OS® 10.7 and above Solaris® 9, 10 HP-UX® 11 v2 IBM® AIX® 5 Red Hat® Fecora® Core 15-17 Red Hat Enterprise 4 and 5 openSUSE® 11 and 12 Ubuntu® Unix®

Xerox® Color C60/C70 Printer

Print Drivers Supported	<p>Please refer to www.xerox.com/support for specifics. As new operating system versions are added, support is also added for Xerox® C60/C70 Color Printer. Also note that there is more than one print driver based on the configuration purchased (e.g. digital front ends, Xerox® Global Print Driver)</p> <p>Windows Vista, 32-bit, SP2 Windows Vista, 64-bit, SP2 Windows 7, 32-bit Windows 7, 64-bit Windows 8, 32-bit Windows 8, 64-bit Windows 8.1 Update 1, 32-bit Windows 8.1 Update 1, 64-bit Windows 10, 32-bit Windows 10, 64-bit Windows Server 2008, 32-bit Windows Server 2008, 64-bit Windows Server 2008 R2, 64-bit Windows Server 2012, 64-bit Windows Server 2012 R2, 64-bit Citrix® XenApp 5.0, 6.0 and 6.5 Citrix XenDesktop 7.6 Novell Netware 6.x: NDPS, NDS, iPrint Novell Open Enterprise Server Cluster: Windows Server 2008 32- and 64-bit, 2008 R2, 64-bit; Server 2012 64-bit; 2012 R2 64-bit Xerox® Mobile Express Driver® XPS Print Driver Xerox® Global Print Driver®</p>
Features	<ul style="list-style-type: none"> • Automatic two-sided • Bi-directional Print Drivers provide device and job status • Custom Macintosh Driver (Watermark, Booklet Creation, JBA, Secure, Sample, Delay Print) • Secure print • Delay print • Embedded Web server for remote control/monitor/setup • Enhanced Gloss • Sample set • Booklet creation • Cover selection • Paper selection by attribute • N-up • Watermarks • Banner sheets • Fit to new paper size • Output tray selection • Print calibration • Print from USB <p>Plus more!</p>
Connectivity	Ethernet interface (10 MBTX / sec, 100 MBTX / sec, 1000 MBTX / sec)
	For more information, go to www.xerox.com/C70IntegratedColorServer .
Additional Print Server Options	
Xerox® EX-i C60/C70 Print Server Powered by Fiery®	
Hardware/Platform	<ul style="list-style-type: none"> • Fiery® FS200 software • Intel Pentium G1820 Processor (2.7 GHz) • Performance optimized by proprietary combination of EFI Technology, VX600 ASIC and software
Memory	2 GB
Hard Drive	500 GB
Server Operating System	Linux®
Print Languages (PDL)	Adobe® PostScript® 3™ (v3019), PCL 6C (emulation), Adobe Acrobat 9
Features	<ul style="list-style-type: none"> • Productivity starts with a fast RIP. The Integrated Fiery Color Server enables you to print large and/or complex Microsoft® Office® documents, PowerPoint® files and color-critical PDFs accurately and quickly. • Simplify and streamline your workflow. Automate job submission of repetitive job types to achieve productive, error-free workflows with Hot Folders and Virtual Printers. • Take advantage of commonly used Fiery presets to save time when submitting jobs. With Fiery server technology, even novice users can perform complex jobs using the pre-set drivers configured for the task. • Get the color right. Produce precise, exact color from all applications, platforms and formats with Fiery color management tools. • Turn up the impact with variable information. Customize your output to a specific audience with varying text, photos and graphics with the Integrated Fiery Color Server's basic variable data printing capabilities.
Connectivity	Direct Connection (Single IP)

Xerox® Color C60/C70 Printer

Fiery Productivity Package Option	<ul style="list-style-type: none"> • Fiery JDF • Graphic arts filters for Hot Folders • Fiery Image Enhance Visual Editor • Fiery ImageViewer • Postflight report • Control bar • Configurable auto trapping • Paper simulation
	For more information, go to www.xerox.com/C70EXiFieryColorServer .
Xerox® FreeFlow® Print Server Integrated for the Xerox® Color C60/C70 Printer	
Processor	Intel® Dual Core Pentium G3420 Processor
Memory (ESS)	16 GB
System Disk	1 TB 7200 SATA or equal
Print Languages (PDL)	<p>Adobe® PostScript® Level 1, 2, 3 PDF up to version 1.7 (Acrobat XI), including PDF/VT-1 specification version 1.1, PDF/X-1a, PDF/X-3 and PDF/X-4 EPS TIFF v6, native and multi-page (TIFF-IT is not supported) Xerox® Variable-data Intelligent PostScript Printware (VIPP) (license required) Jobs submitted from Xerox® FreeFlow® Workflow Offerings Compatible with Xerox® FreeFlow Variable Information Suite Version 9.0 JPEG Microsoft Word and PowerPoint documents XPS IPDS (license required) PPML</p> <p>The following file formats are not supported: ASCII PCL</p>
Features	<p>Simple</p> <ul style="list-style-type: none"> • Windows 7 platform for a familiar experience • Integrated / Busted setup. Perfect for small footprint and quick and easy site setups • Accepts Native Microsoft Office® files for Direct Print (from walk-up USB PowerPoint®, for example) <p>Productive</p> <ul style="list-style-type: none"> • All the advantages of a Xerox Production workflow – delivered in a value-oriented solution • Streamlined drag/drop submission from tablets and more <p>Powerful</p> <ul style="list-style-type: none"> • Bring the power of Xerox® patented RIP technology in a value oriented solution • Latest direct Adobe PDF Print Engine and GC credentials included • Includes Variable Data Print / Color Management / Production Workflows <p>Tints and Highlights fine-tuned for better accuracy Duotone, Tri-tone and Quad-tone support</p> <ul style="list-style-type: none"> • Spot Color Editor • Calibration and Profiling with XRite i1, Pro2 (optional) • Job Accounting reporting • Custom Paper Catalog • IPDS and PPML • Faster job programming with 'Select by Tray' job programming • Simplified and intuitive job recovery • Enhanced imposition
Connectivity	Direct Connection (Single IP)
	For more information, go to www.xerox.com/C70FreeflowPrintServer .
Xerox® EX C60/C70 Print Server Powered by Fiery®	
Processor	Intel® Core™ i5-4570S Processor 2.9 up to 3.60 GHz with Turbo, Quad Core Performance optimized by proprietary combination of EFI technology, VX600 ASIC and software
Memory (ESS)	4 GB
System Disk	1 TB
Print Languages (PDL)	<p>Adobe PostScript® Level 1, 2, 3; PDF/X-1a, 3 and 4; EPS; Adobe Acrobat® 9.1, Native PDF 1.3, 1.4, 1.5, 1.6 and 1.7; CT/LW; TIFF, TIFF/IT, DCS2, JPEG Microsoft Native Formats (DOC, XLS, PUB, PPT) enabled through Fiery Hot Folders feature EFI™ FreeForm 1, and FreeForm 2 VDP</p>

Xerox® Color C60/C70 Printer

Features	<ul style="list-style-type: none"> • Job-based Calibration Integration <ul style="list-style-type: none"> – Fiery Spot-On finds the best match of PANTONE®, PANTONE Series, RGB, CMYK, L*a*b* and Spot Colors – Color Modes for professional proofing and enhanced production color requirements – Maximum print density • Fiery Graphic Arts Package, Premium Edition (optional) provides expert tools for preflighting and troubleshooting jobs • Fiery Color Profiler Suite (optional) creates, verifies and edits color profiles with a single profiling solution • Fiery technology increases your profits by delivering high-impact documents with vibrant images and color that exceed your customers' expectations and also meets tight turnaround times and allows you to do more work by automating manual tasks and removing bottlenecks that slow down production. • With Fiery technology, you can produce effective marketing pieces with the widest range of output options, including automatic identification of job elements such as text, images and spot colors. This feature also eliminates the need to re-program jobs, making the process simple and quick. It is ideal for producing powerful marketing materials, personalized communications and packaging and photo publishing applications. • Fiery ColorWise gives high-quality color out-of-the-box and integrates the essential components of Fiery Graphic Arts Package, Premium Edition, Fiery Spot-On and the Fiery Color Profiler Suite to control and manage color throughout your workflow. • The Fiery Command WorkStation increases your production and reduces errors and waste by centralizing job management via its intuitive user interface. Simplify your labor-intensive document composition and imposition tasks even more by using Fiery SeeSequence Impose and Compose's intuitive interface. • Fiery JDF technology connects EFI solutions and Fiery-enabled solutions, so you can move job information through your system faster and more efficiently. By supporting the Adobe PDF Print Engine, Fiery servers also offer a native end-to-end PDF workflow, therefore improving the consistency and flexibility of your printed output from design to print. • Using Fiery servers and Fiery Command Workstation, you get a new level of integration for process and profit improvement, including seamless connectivity to Xerox® FreeFlow® for workflow automation. 		
Connectivity	Direct Connection (Single IP), Network Switch, (Dual IP)		
	For more information, go to www.xerox.com/C70EXPrintServer .		
Supplies	Description	Yield	Part Number
Customer Replaceable Items			
Toner Cartridges (Metered)	Black	30,000 pages ⁴	006R01521
	Cyan	34,000 pages ⁴	006R01524
	Magenta	32,000 pages ⁴	006R01523
	Yellow	34,000 pages ⁴	006R01522
Toner Cartridges (Sold)	Black	30,000 pages ⁴	006R01655
	Cyan	34,000 pages ⁴	006R01656
	Magenta	32,000 pages ⁴	006R01657
	Yellow	34,000 pages ⁴	006R01658
Black Drum Cartridge	1 Cartridge	190,000 pages ⁴	013R00663
Color Drum Cartridge	1 Cartridge per Color	85,000 pages ⁴	013R00664
Charge Corotron	For Black Drum	190,000 pages ⁴	013R00650
Fuser	110V	200,000 pages ⁴	008R13102
	220V	200,000 pages ⁴	008R13065
Waste Toner Container	1 Cartridge	50,000 pages ⁴	008R12990
Feed Roll Kits	1 Assembly	300,000 pages ⁴	008R13169
Staple Cartridges	For BR Finisher and Convenience Stapler (1 cartridge per carton)	5,000 each cartridge	008R12964
	For BR Booklet Maker Finisher (4 cartridges per carton)	5,000 each cartridge	008R13177
	Staple Cartridge and Waste Container for Standard Finisher	5,000 each cartridge	008R13041
Staple Refills	For BR Finisher, BR Booklet Maker Finisher and Convenience Stapler (3 refills per carton)	5,000 each refill (15,000 total)	008R12941

¹ Maximum volume capacity expected in any one month. Not expected to be sustained on a regular basis.

² Expected regular monthly throughput.

³ Paper capacities are based on 20 lb. / 75 gsm stock; capacities will vary with different weight stocks.

⁴ Approximate pages. Declared Yield based on 5 page job size, 30% color and 70% Black and white ratio, using letter / A4 media. Yield will vary based on media size, image area coverage, job run length, media orientation and usage patterns.

To view a product video, visit www.xerox.com. Build and configure your own Xerox® Color C60/C70 Printer at www.buildyourownxerox.com.

